

Figure 3: Showing the URL in the absence of the application

To query the version, type:

```
cat /sys/kernel/adk_linux/aoa_init/version
```

Send the identity strings as follows:

```
echo "manufacturer=Nexus-Computing GmbH" > /sys/kernel/
adk_linux/aoa_init/identity
echo "model=Simple Slider" > /sys/kernel/adk_linux/
adk_linux/aoa_init/identity
echo "version=0.1" > /sys/kernel/adk_linux/aoa_init/
identity
```

likewise you can also send "description=A Simple Slider", "URL=http://www.nexuscomputing.ch/SimpleAccessory.apk" and "serial=1337", but optional

Start the device in audio/accessory mode:

```
echo "audio" > /sys/kernel/adk_linux/aoa_init/start
echo "accessory" > /sys/kernel/adk_linux/aoa_init/start
```

This driver also supports initialisation through ioctl operations with custom strings, or with module parameter `init_on_probe=1` with default identity strings. Please refer to the wiki page of gitrepo for more details about the driver.

At this moment, if a suitable app is installed, a pop-up




Figure 4: SimpleAccessory application of `/sys/class/backlight/acpi_video0/brightness`, as an example. A sample code (*backlight-demo.c*) to work with a skeleton driver is kept under the 'Examples' section of gitrepo. Also, with other examples like *aoa-read-dump.c*, *simple-demo.c*, etc, you can read raw data coming from the app. In this case, a value between 0 to 255 will be printed each time slider moves.

Similarly, to work with the ADK 2012 app, you can send `Manufacturer=Google, Inc., Model=DemoKit, Version=2.0` as identity strings.

If you have any difficulties in building or loading the kernel space module, you can customise libusb-based user space codes like *linux-adk* by Gary Bisson or *usbAccReadWrite.c* by Jeremy Rosen, according to the requirements of your own Android apps. 

References

- [1] <http://source.android.com/accessories/>
- [2] 'Leveraging the Android Accessory Protocol' by Gary Bisson, <http://github.com/gibsson/linux-adk>
- [3] Chapter 5: 'USB Accessory' from the book 'Unboxing Android USB' by Rajaram Regupathy
- [4] Contents of Google I/O 2011 and 2012

By: Rajesh Sola

The author is a faculty member of C-DAC's Advanced Computing Training School, Pune, in the embedded systems domain. You can reach him at rajeshsola@gmail.com.

● TechnoMail
Enterprise Email Solutions

● TechnoMail Cloud
Zero Capital Email Solution

TechnoInfotech®

info@technoinfotech.com
www.technoinfotech.com

● High Volume SMTP Solutions
(Hosted and on-Premise)

● Business Promotion Mailing
(Hosted and on-Premise)