



Figure 1: Load balancing using the Pound server



Figure 2: Default page

```
[root@apachewebserver1 Packages]#
```

Start the service:

```
[root@apachewebserver1 ~]# service httpd start
Starting httpd:
[ OK ]
[root@apachewebserver1 ~]#
```

Start the service at boot time:

```
[root@apachewebserver1 ~]# chkconfig httpd on
[root@apachewebserver1 ~]#
[root@apachewebserver1 ~]# chkconfig --list httpd
httpd          0:off  1:off  2:on   3:on   4:on   5:on
6:off
[root@apachewebserver1 ~]#
```

The directory location of Apache HTTP Service is `/etc/httpd/`. Figure 2 gives the default test page for Apache Web Server on Red Hat Enterprise Linux.

Now, let's create a Web page `index.html` at `/var/www/html`. Restart Apache Web Service to bring the changes into effect.

The `index.html` Web page will be displayed (Figure 3).

Repeat the above steps for Web Server2

ApacheWebServer2.linuxrocks.org, except for the following:

- Set the IP address to 192.168.10.32
- The contents of the custom Web page 'index.html' should be '...ApacheWebServer2...' as shown in Figure 4.



Figure 3: Custom web page of Apache Web Server1

Figure 4: Custom web page of Apache Web Server2

Installation and configuration of Pound gateway server

First, ensure YUM is up and running:

```
[root@poundgateway ~]# ps -ef | grep yum
root      2050   1998   0 13:30 pts/1    00:00:00 grep yum
[root@poundgateway ~]#
```

```
[root@poundgateway ~]# yum clean all
```

Loaded plugins: product-id, refresh-packagekit, subscription-manager

Updating Red Hat repositories.

Cleaning repos:

Cleaning up Everything

```
[root@poundgateway ~]#
```

```
[root@poundgateway ~]# yum update all
```

Loaded plugins: product-id, refresh-packagekit, subscription-manager

Updating Red Hat repositories.

Setting up Update Process

No Match for argument: all

No package all available.

No Packages marked for Update

```
[root@poundgateway ~]#
```

Then, check the default directory of YUM:

```
[root@poundgateway ~]# cd /etc/yum.repos.d/
[root@poundgateway yum.repos.d]#
[root@poundgateway yum.repos.d]# ll
total 8
-rw-r--r-- 1 root   root   67 Jul 27 13:30 redhat.repo
-rw-r--r-- 1 root   root  529 Apr 27 2011 rhel-source.repo
[root@poundgateway yum.repos.d]#
```

By default, the repo file 'rhel-source.repo' is disabled. To enable, edit the file 'rhel-source.repo' and change the value

```
enabled = 1
```

or

```
enable = 0
```

For now you can leave this repository disabled.