



Convert images to PDF

Often, your scanned copies will be in an image format that you would like to convert to the PDF format. In Linux, there is an easy-to-use tool called *convert* that can convert any image to PDF. The following example shows you how:

```
$convert scan1.jpg scan1.pdf
```

To convert multiple images into one PDF file, use the following command:

```
$convert scan*.jpg scanned_docs.pdf
```

The 'convert' tool comes with the *imagemagick* package. If you do not find the *convert* command on your system, you will need to install *imagemagick*.

—Madhusudana Y N,
madhusudanayn@gmail.com



Your own notepad

Here is a simple and fast method to create a notepad-like application that works in your Web browser. All you need is a browser that supports HTML 5 and the commands mentioned below.

Open your HTML 5 supported Web browser and paste the following code in the address bar:

```
data:text/html, <html contenteditable>
```

Then use the following code:

```
data:text/html, <title>Text Editor</title><body  
contenteditable style="font-size:2rem;line-height:1.4;max-  
width:60rem;margin:0 auto;padding:4rem;">
```

And finally...

```
data:text/html, <style>html,body{margin: 0; padding: 0;}</  
style><textarea style="font-size: 1.5em; line-height:  
1.5em; background: #233000; color: #233a3; width: 100%;
```

```
height: 100%; border: none; outline: none; margin: 0;  
padding: 90px;" autofocus placeholder="wake up Neo..." />
```

Your Web browser-based notepad is ready.

—Chintan Umarani,
chintan4u@in.com



How to find a swap partition or file in Linux

Swap space can be a dedicated swap partition, a swap file, or a combination of swap partitions and swap files.

To find a swap partition or file in Linux, use the following command:

```
swapon -s
```

Or...

```
cat /proc/swaps
```

...and the output will be something like what's shown below:

Filename	Type	Size	Used	Priority
/dev/sda5	partition	2110460	0	-1

Here, the swap is a partition and not a file.

—Sharad Chhetri,
admin@sharadchhetri.com



Monitoring a process in Linux

To monitor the system's performance on a per-process basis, use the following command:

```
pidstat -d -h -r -u -p <PID> <Delay in seconds>
```

This command will show the CPU utilisation, memory utilisation and IO utilisation of the process, along with the PID. Example: