

TCP window size: 16.0 KByte (default)

```
[ 3] local 192.168.1.109 port 39572 connected with
192.168.1.100 port 5001
```

```
AC[ ID] Interval      Transfer    Bandwidth
[ 3]  0.0- 6.3 sec  6.38 MBytes 8.51 Mbits/sec
```

By default, the *iperf* client connects to the *iperf* server on the TCP port 5001 and the bandwidth displayed by *iperf* is the bandwidth from the client to the server. In the above example, it is 8.51 Mbits/sec between two Linux test systems connected over a wireless network.

—Prasanna,  
prasanna.mohanasundaram@gmail.com

## Power yourself with Netstat



Here are a few uses of the *netstat* command that can help you.

To display the kernel interface table:

```
netstat -i
```

To display the kernel routing table:

```
netstat -rn
```

To display all open network sockets:

```
netstat -uta
```

To display network statistics:

```
netstat -s
```

—Prasanna,  
prasanna.mohanasundaram@gmail.com

## Finding the full path of the shell command



There is a command named *which* that takes one or more arguments as input. It prints to standard output the full path of the shell command. It does this by searching for an executable or script in the directories listed in the environment variable *PATH*:

```
[aarsh@localhost ~]$ which poweroff
```

```
/usr/bin/poweroff
```

If the command is not found, it gives the output shown below:

```
[aarsh@localhost ~]$ which module
```

```
/usr/bin/which: no module in (/usr/lib/qt-3.3/bin:/usr/
kerberos/sbin:/usr/kerberos/bin:/usr/lib/ccache:/usr/local/
bin:/usr/bin:/bin:/usr/local/sbin:/usr/sbin:/sbin:/home/aarsh/
bin)
```

—Aarsh S Talati,  
aarshstlati1989@gmail.com

## Securing files



Here is a simple tip to password protect your files:

```
vi -x test
```

This command will ask for an encryption key. You have to type the key twice. Then save and quit the opened file.

Now, whenever you open this file, it will ask for that password first.

—Sumit Chauhan,  
sumit1203@gmail.com

## Uninstalling a package



To completely uninstall a package, first check the exact name of the package to be uninstalled by using the following command:

```
sudo dpkg --get-selections | grep package_name
```

The output of the above command will display the name of the package.

Once you know the package name, you can remove it by using the command shown below:

```
sudo apt-get remove --purge package_name
```

—Neeraj Joshi,  
neeraj88joshi@gmail.com

END

## Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in OSFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at [www.linuxforu.com](http://www.linuxforu.com). The sender of each published tip will get a T-shirt.