

Figure 1: Features of Nagios




Figure 2: Nagios Checker settings




Figure 3: Status script URL




Figure 4: Nagios Checker status

and third-party add-ons—help users gain valuable understanding.

## Use cases

Nagios can be effectively used for network monitoring at ISPs, in government, health care, manufacturing, banking and finance, telecommunications, etc.

As an example of getting Nagios to monitor a system, let's install it in an OpenSUSE Virtual Machine. We can use VMware Workstation, Player or any other product to create the VM. Install OpenSUSE 12.2 in it. When that's done, install some pre-requisite packages using the Zypper command-line package manager, with the following commands:

```
zypper install kernel-source make gcc gcc-c++
zypper install rrdtool php5 php5-gd php5-zlib apache2-mod_php5
perl-SNMP net-snmp-32bit nmap ncftp libwpavpack1 apache2
```

Download Nagios Core into the VM, from [www.nagios.org/download/](http://www.nagios.org/download/). Log in as `root`, create a user and groups for *Nagios*, and change the user password:

```
# /usr/sbin/useradd -m nagios
# passwd nagios
Changing password for nagios.
New Password:
Password changed.
# groupadd nagcmd
# groupadd nagios
```

Add the nagios user to the *nagcmd* and *nagios* groups, as follows:

```
# usermod -G nagcmd nagios
```

Extract the Nagios Core tar file; *cd* to the extracted folder, and run the following command:

```
# ./configure --with-command-group=nagcmd
# make all ##If successful, ends with an "Enjoy!" message.
```

Install *init* scripts, and sample config files in `/usr/local/naqios/etc`:

```
# sudo make install-init
/usr/bin/install -c -m 755 -d -o root -g root /etc/rc.d
/usr/bin/install -c -m 755 -o root -g root daemon-init /etc/rc.d/
nagios
*** Init script installed ***
# make install-config
```

Install and configure permissions on the directory: