

Get the directory size from the terminal

 Getting the size of the directory is easy with the `du` command, but if you want to get the size of all files in the directory which should not include the sub-directory, you can use the command given below:

```
$ls -hs | head -1
```

This will give you the desired size.

—Kousik Maiti,
kousikster@gmail.com

Adding the 'Eject' command to your menu

 Sometimes it gets difficult to eject the CD ROM on your Linux-based computer. Here is a tip that allows you to add the Eject command to your menu.

Create a file called *Eject CD* in `$HOME/.gnome2/nautilus-scripts/` directory. Now open a file in any text editor and type the following code:

```
#!/bin/bash
eject /dev/sr0/
```

Here `sr0` is the device name of the CD ROM Drive.

Save and close the file.

Next, provide 'execute' permission to the newly created script:

```
$ chmod $HOME/.gnome2/nautilus-scripts/Eject\ CD
```

Now you can eject the CD from the pop-up menu displayed by right clicking on the menu.



Note: Before ejecting the CD, be sure that no program is using the CD ROM drive, because the drive does not give any error if it fails to eject the CD.

—Vivek Marakana,
vivek.marakana@gmail.com

Execute your jobs without a hurdle

 Here is a tip that will help you to keep executing jobs even after exiting the shell.

You can use the 'disown' command to run a job after you've logged out. It releases all the running jobs from ownership. You can also use the 'nohup' command, but for that, you have to specify in advance as shown below:

```
$ nohup nmap -vv -sP 10.13.37.1/24 &
```

You can now log out from the terminal. Your command

will keep executing and the output will be in `nohup.out`

The same can also be achieved by using 'disown' as shown below:

```
$ nmap -vv -sP 10.13.37.1/24 -oN VizOutput.txt
```

Now press...

`Ctrl+Z`

This will suspend the running job.

After suspending the job, run the following command:

```
$ disown
```

Now you can log out from the terminal without killing the job.

—Vizay Soni,
Vs4vijay@gmail.com

Linux monitoring tools

You can use various Linux tools to collect systems statistics like CPU usage, memory usage, IO for hard disks, etc. A few of these are listed below:

1. `top` – A well known command for listing the running process with CPU and memory usage.
2. `vmstat` – Provides all virtual memory related information.
3. `iostat` – Provides IO statistics of devices and other CPU statistics.
4. `free` – This command displays the free, used, buffered or cached memory.
5. `dstat` – This is a good command to collect all the statistics in one place. It is a combination of `vmstat`, `iostat` and the `netstat` commands.
6. `netstat` – This displays the routing table, network interface statistics and ports opened by the process.

—Prasanna,
prasanna.mohanasundaram@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get an LFY T-shirt.