

Buttons and widgets: Just as we created various lists using different attributes, in order to create basic link-based buttons, the attribute used within `<a href=" " " is data-role="button"`. For a disabled button, add a `class="ui-disabled"` attribute.

Form buttons: The framework automatically converts any button or input element with a type of `submit`, `reset`, etc; there is no need to add a `data-role="button"` attribute for this—you can directly call the Button plug-in just like any JQuery plug-in, as follows:

```
$('[type="submit"]').button();
```

By calling the plug-in, you will get the enhanced buttons. To prevent a form button from being converted into an enhanced button, add the `data-role="none"` attribute, and the native control will be rendered.

Button plug-in based buttons: We can create buttons using normal HTML also, such as:

```
<button>Click Me</button>
<input type="Submit" value="Submit button">
<input type="Reset" value="Reset button">
```

Creating buttons with icons: We can add buttons with some pre-defined icons, which helps to specify the use of the button in a better way. For example:

```
<a href="index.html" data-role="button" data-
icon="delete">Delete</a>
```

Various types of icons can be embedded, like the left and right arrows. You can check various types at <http://jquerymobile.com/demos/1.2.0/#/demos/1.2.0/docs/buttons/buttons-icons.html>. Some buttons can be seen in Figure 4.

Form elements: Input types: The framework supports various input types. Some of them are given below:

```
<label for="basic">Text Input:</label>
<input type="text" name="name" id="basic" value="" />
```

Text-areas: This element should be wrapped inside `data-role="fieldcontain"`:

```
<label for="textarea-a">Textarea:</label>
<textarea name="textarea" id="textarea-a">
```

Search input: For creating the search bar, `input type="search"` can be used:

```
<input type="search" name="search" id="search-basic" value="" />
```

The slider:

```
<form>
<label for="slider-0">Input slider:</label>
```




Figure 3: List and checkboxes

```
<input type="range" name="slider" id="slider-0" value="25"
min="0" max="100" />
</form>
```

Radio buttons:

```
<fieldset data-role="controlgroup">
<input type="radio" name="radiobutton" id="button1"
value="1" />
<label for="button1">Male</label>
<input type="radio" name="radiobutton" id="button2"
value="2" />
<label for="button2">Female</label>
</fieldset>
```

Checkboxes:

```
<label>Subscribe</label>
<input type="checkbox" name="checkboxbox1" /> Linux For You
</label>
<input type="checkbox" name="checkboxbox2" id="checkboxbox2"
class="custom" />
<label for="checkboxbox2">Electronics For You</label>
```

By practising with these widgets, you can build a basic yet attractive UI. Lots of things like themes, transitions, toolbars, dialogue boxes and pop-ups are still left; I will cover them in the next part of the article. I am also exploring the JQuery Mobile framework in depth these days, and will share my findings with you. Suggestions and queries are always welcome. **END**

Anupriya Sharma

The author has just graduated and is currently working in the Android department of a reputed MNC. She loves Android and iOS development, yet still manages some time for cooking, dancing and her all-time favourite, shopping. You can contact her at anupriyasharma2512@gmail.com.