

```
class IDepartment(form.Schema):
    """
    Departments
    """
    title = schema.TextLine(
        title=_(u"Name"),
    )
    description = RichText(
        title=_(u"A short description"),
    )
    image = NamedImage(
        title=_(u"Head of Department"),
        description=_(u"Please upload an image"),
        required=False,
    )
```

You can find information about various data types in Dexterity documentation on the plone.org site.

The `IWriter` class in `writer.py` will become what follows:

```
from zope import schema
from plone.app.textfield import RichText
from plone.namedfile.field import NamedImage
from z3c.relationfield.schema import RelationChoice
from plone.formwidget.contenttree import ObjectPathSourceBinder
from lfy.demo.department import IDepartment

class IWriter(form.Schema):
    """
    Writers
    """
    title = schema.TextLine(
        title=_(u"Name"),
    )
    department = RelationChoice(
        title=_(u"Department"),
        source=ObjectPathSourceBinder(object_provides=IDepartment.__
identifier__),
    )
    profile = RichText(
        title=_(u"Profile"),
    )
    blog = schema.URI(
        title=_(u"Blog Site"),
        required=False,
    )
    picture = NamedImage(
        title=_(u"Picture"),
        description=_(u"Please upload an image"),
        required=False,
    )
```

You may want to change the default behaviour so that the system does not add metadata fields like title. This is achieved by deleting the line below from the `lfy.demo.department.xml` and `lfy.demo.writer.xml` files in the `profiles/default/types` sub-directory.

```
<element value="plone.app.dexterity.behaviors.metadata.IBasic"/>
```

You are now ready to build the Plone instance with the custom fields. Edit the `buildout.cfg` file to add the `lfy.demo` egg:

```
eggs =
    ...
    lfy.demo

develop =
    src/lfy.demo
```

Stop `plone`, build the new instance and start it again.

```
$ bin/plonectl stop
$ bin/buildout
$ bin/plonectl start
```

As an admin user, enable Dexterity types, and the demo application you have just created, in the ‘Add-ons’ from ‘Site Preferences’. The ‘Add new’ option will now have `Department` and `Writer` as additional types.

Changing the view

The default view is reasonable, but each field is stacked below the other. A URL is shown as text, and not as a link. You can replace the default view of the writer by your own custom view. In `writer.py`, in the class ‘`SampleView`’ uncomment the following line:

```
grok.name('view')
```

Now, `SampleView` becomes the default view. You will need to modify the corresponding template, `sampleview.pt`, in the sub-directory `writer_templates`. The template’s logic is in the `metal:main` block, which you may replace as follows, so that the profile wraps around the image:

```
<metal:main fill-slot="main">
    <tal:main-macro metal:define-macro="main">
        <h1 class="documentFirstHeading" tal:content="context/title" />
        <!-- illustrates creating a link from a relation object -->
        <div>
            <p><label>Department</label>
            <a tal:attributes="href string:${context/department/
to_path}"
                tal:content="context/department/to_object/title"><link/>
```