

the nice value of the process 'named'. This denotes that the 'named' process value has a normal priority.

To reduce the priority of the said process further, the below command can be used. This will reschedule the 'named' process with the nice value of 10.

```
#nice --10 named
# ps axl | grep named
```

The output will be:

```
0      0  9908  8733  18    10  61164   736 pipe_w SN   pts/1
0:00 grep named
```

—Vinod Rana,
vkumar@hughes.in

Use the screen program in UNIX



The screen program allows you to use multiple windows (i.e., virtual terminals) in UNIX.

To start screen, enter the following command:

```
#screen
```

This is very useful in cases where you access a UNIX machine, remotely, using 'putty' and want to create multiple virtual terminals within a single 'putty' session.

For example, you can start a long running process this way:

```
# screen
```

Run any command such as 'rsync' or 'scp' and then press 'ctrl+a' and then 'd'. This will detach the screen.

You can terminate the 'putty' session while the process is running on the target machine.

Now, if you want to resume the session and see the progress, you can run the following command to start from where you left it.

```
# screen -r
```

For other options, refer to 'man screen'.

—Vishwanath Hariharan,
vishi83@gmail.com

Unlock more space from your hard drive



When you format a partition in GNU/Linux, 5 per cent of the total space gets reserved for privileged processes, by default. This is done so that systems processes continue to function correctly, if the filesystem gets full. This is useful for your 'root' partition.

However, if you have a 50 GB separate 'Home' partition, you may want to make use of a little more storage space by reducing the percentage of the reserved space. You can use the 'tune2fs' command to change the default allocation of space reserved for privileged processes.

```
#tune2fs -m 1 /dev/sda6
```

The above command changes the reserved space for privileged processes on '/dev/sda6' to 1 per cent. You can see the effected change by mounting the filesystem and checking the available space using the 'df' command before and after you execute the above command.

—Sumit Rai,
sumitrai96@gmail.com

Count the number of lines in the file



Create a sample file:

```
$echo "Linux" > file.txt
$echo "For" >> file.txt
$echo "You" >> file.txt
```

To display file content, use the following command:

```
$cat file.txt
Linux
For
You
```

Type the following command to count the number of lines in a file:

```
$cat file.txt | wc -l
3
```

This can be very useful while working with the Shell script.

—Narendra Kangralkar,
narendrakangralkar@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get an LFY T-shirt.