

2. Copy `$HOME/.ssh/id_rsa.pub` to the server (the computer where you need to log in).
3. On the server, run the following commands:

```
$ cat id_rsa.pub >> $HOME/.ssh/authorized_keys2
$ chmod 0600 $HOME/.ssh/authorized_keys2
```

Depending on the version of OpenSSH, the following commands may also be required:

```
$ cat id_rsa.pub >> $HOME/.ssh/authorized_keys
$ chmod 0600 $HOME/.ssh/authorized_keys
```

An alternative is to create a link from the `'authorized_keys2'` to `'authorized_keys'` command:

```
$ cd $HOME/.ssh && ln -s authorized_keys2 authorized_keys
```

4. On the client, test the results by 'ssh'ing to the server:

```
$ ssh -i $HOME/.ssh/id_rsa server
```

5. Optional: Add the following `'$HOME/.ssh/config'` on the client:

```
Host server
IdentityFile ~/.ssh/id_rsa
```

This allows 'ssh' access to the server without having to specify the path to the `'id_rsa'` file as an argument to 'ssh' each time.

—Navneet Kataria,
ennavneet@yahoo.com

How to see all the applications that are using the Internet



To see the list of applications using the Internet at any point of time, go to the console and type in the following:

```
lsof -P -i -n
```

The output will show you the details of the connected applications.

—Nitish Upreti,
nitishupreti@gmail.com

Another way to reset the root password



In some Linux distros, including Ubuntu, when you go into recovery mode from the Grub menu to reset the password for the `root` as well as other users, you may be asked for the `root` password. To remove the `root` password, boot from the live CD and open the `'/etc/passwd'` file by running the following command at the terminal:

```
#vi /etc/passwd
```

```
root:x:0:0:root:/root:/bin/bash
```

```
...
```

```
.
```

```
.
```

```
kousik:x:1000:1000:kousik,,:/home/kousik:/bin/bash
```

Here ':' is a separator. The first field (kousik) is the user name and the second field is the password, denoted by 'x'. The actual password is stored in `'/etc/shadow'` file in the encrypted format. Remove the 'x' from the users whom you want to reset passwords for. Then reboot and log in via 'TTY's' by pressing `'Alt+F1'`. It will prompt you for the user name. Just give the user name and press 'Enter'. It will take you to the 'bash' prompt.

From here you can change the password by using the following command:

```
#password
```

—Kousik Maiti,
kousikster@gmail.com

Stopping a running process



When you get stuck in any process which can't stop with 'force-quit', you can try stopping it from the 'terminal' window. To stop a process or application from the 'terminal', you need to know the PID of the process so that you can kill that PID.

Given below are the set of commands that will stop a running process.

```
#ps -e
```

This will give the details of all processes that are running. Now we need to get the process ID (PID) of the application that we need to stop. For example, assume you are running Firefox on the system.

```
#ps -e | grep firefox
```

The above command will give you the PID of Firefox (which is '9' in this case). Now, this PID can be used as below to stop Firefox.

```
kill -9 PID
```

—Vivek V Pandya,
v2vpan@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get an LFY T-shirt.