

Tyrone®

A solution **flexible** enough to
adapt to your requirements



UP TO 2GBps - UP TO 1 PB - SRP Support

Unified NAS & SAN

Flexible Host Interface

Supports Gigabit Ethernet, 10G Ethernet, FC, Infiniband -- SDR (10Gbps)/ DDR (20Gbps)/ QDR (40Gbps), as individual connectivity options or in combination.

Scalable Storage

Starting from a few TB's FS2 can scale upto 1 PB of storage by using Tyrone expandable solutions.

Block-Storage/SAN Protocols

iSCSI target, FC target, SRP target (over Infiniband)

Supported Clients

Windows, Linux, VMWare ESX/ESXi, FreeBSD*, Solaris, Unix*

(*No SRP Support)

Redundancy/ Fault-Tolerance

Power-supply, Host interface failover, RAID 6 (various level of RAID supported), Multiple Snapshots with scheduling, Volume/ Share Replication, Remote Replication (Block level replication to a 2nd unit with failover/high availability)

Supports Virtual Tape Library*

Do call or write to us for more details.

Netweb
TECHNOLOGIES
ISO 15513:2006 Certified

Corporate Office
B-1/A25, 2nd Floor
Mohan Co-Operative Industrial Estate
Mathura Road, New Delhi - 110044

Website : www.netwebindia.com
www.tyroneystems.com

Email : info@netwebindia.com
netweb@vsnl.com

New Delhi : +91 11 42340000/29942258
Bangalore : +91 80 40540000/41146565
Chennai : +91 44 43531009/26631975
Hyderabad : +91 40 40269635
Kolkata : +91 33 23232055/23232056
Mumbai : +91 22 40158811/40158815
Singapore : +65 65479591/65478592