

REGISTER THIS TEMPLATE DEFINITION!

}

This template further uses a template called *generic-host*, which is also defined in the same file, as:

```
define host{
    name generic-host          ; The name of this host
template
    notifications_enabled 1    ; Host notifications are
enabled
    event_handler_enabled 1 ; Host event handler is enabled
    flap_detection_enabled 1 ; Flap detection is enabled
    failure_prediction_enabled 1 ; Failure prediction is
enabled
    process_perf_data 1      ; Process performance
data
    retain_status_information 1 ; Retain status
information across program restarts
    retain_nonstatus_information 1 ; Retain non-status
information across program restarts
    notification_period 24x7    ; Send host
notifications at any time
    register 0                  ; DONT REGISTER
THIS TEMPLATE DEFINITION!
}
```

Other objects referenced in the above snippets are:

- a) *contact_groups* called '*admins*'
- b) *notification_period* called '*workhours*' and '*24x7*'
- c) *check_command* called '*check-host-alive*'

The contact group object called '*admins*' is also defined in the same file:

```
define contactgroup{
    contactgroup_name    admins
    alias                Nagios Administrators
    members               nagios-admin
}
```

The member *nagios-admin* of the above contact-groups is defined as:

```
define contact{
    contact_name          nagios-admin
    alias                 Nagios Admin
    service_notification_period 24x7
    host_notification_period 24x7
    service_notification_options w,u,c,r
    host_notification_options d,r
    service_notification_commands notify-by-email
    host_notification_commands host-notify-by-email
    email                 nagios-admin@localhost
}
```

The time period '*workhours*' is defined as:

```
define timeperiod{
    timeperiod_name workhours
    alias             "Normal" Working Hours
    monday            09:00-17:00
    tuesday           09:00-17:00
    wednesday         09:00-17:00
    thursday          09:00-17:00
    friday            09:00-17:00
}
```

The time period '*24x7*' is defined as:

```
define timeperiod{
    timeperiod_name 24x7
    alias            24 Hours A Day, 7 Days A Week
    sunday           00:00-24:00
    monday           00:00-24:00
    tuesday          00:00-24:00
    wednesday        00:00-24:00
    thursday         00:00-24:00
    friday           00:00-24:00
    saturday         00:00-24:00
}
```

Command definitions are used to define commands that Nagios will use. They can include macros from resource definition files. The command used in the *localhost.cfg* file for *localhost* is defined in */etc/nagios/commands.cfg* as:

```
define command{
    command_name    check-host-alive
    command_line     $USER1$/check_ping -H $HOSTADDRESS$ -w
3000.0,0,00% -c 5000.0,100% -p 1
}
```

\$USER1\$ is a macro defined in */etc/nagios/private/resource.cfg* as a file system path:

```
$USER1$=/usr/lib64/nagios/plugins
```

Once the host, host-groups, commands and time periods have been defined, it is time to define services. For the purpose of this introductory article, we will use only the *ping* service. Again, the service definition sections in the sample configuration file listed below are self-explanatory. We will explore the details of service definitions in later articles.

```
define service{
    use local-service          ; Name of service template to
use
    host_name localhost
```