

brings you to the page you just created. This renders what you type in *Body*, which is just plain HTML (though non-compliant with the HTML specs—it is without proper `<body>` and `<head>` tags).

The header, footer and menu

The header, footer and menu share a common characteristic: they appear on all pages. Here, we create snippets for each of them.

Name: *header_lfy*

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN" "http://
www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" lang="en"
xml:lang="en">
<head>
<meta http-equiv="Content-Type" content="text/html;
charset=UTF-8" />
<meta name="robots" content="index, follow" />
<title>Linux For You!</title>
</head>
<body>
<h2>Linux For You Page!</h2>
```

Name: *menu_lfy*

```
<ul>
<li><a href="/linuxforyou">LFY page</a></li>
<li><a href="http://www.linuxforu.com/">The Original Linux For
You</a></li>
</ul>
```

Name: *footer_lfy*

```
<h2>This is a footer, copyleft</h2>
</body>
</html>
```

The *header_lfy*, *menu_lfy* and *footer_lfy* snippets are pretty much self-explanatory; they are bits and pieces of a single HTML file. However, we now need to tell Radiant the order in which they should appear.

Layouts

Layouts tell Radiant how all components, including the page and snippets we just created, should appear in the final output page. Go to the 'Design' -> 'Layouts' tab, and create a new layout called *layout_lfy*:

```
<r:snippet name="header_lfy" />
<r:snippet name="menu_lfy" />
<r:content />
<r:snippet name="footer_lfy" />
```

The `<r:>` tags are Radiant macros (the macro language is called 'Radius'). `<r:snippet />` renders the selected snippets, similar to `#include` and `include()` in many programming languages. `<r:content />` represents the contents of the page. In this case, `<r:content />` should refer to what is written in the 'linuxforyou' page, so we should associate the layout with the page—go back to 'Content', edit the page 'linuxforyou' and select 'layout_lfy' as the layout.

All done! Once again, visit <http://hostname/linuxforyou> and Radiant should compile the content according to the layout, and show you the complete page we just created. That was easy, wasn't it?

CSS/Javascript

There are two methods to use CSS/Javascript in Radiant: by creating a page, or by using assets to upload the file.

CSS/Javascript by creating a page

1. Create a page.
1. Paste CSS/Javascript into it.
2. Edit the appropriate page content/snippets for `<div>`, `<link>` or `<script>` tags. For example, `<link rel="stylesheet" href="/styles" type="text/css" />`.

CSS/Javascript by using assets

1. Go to 'Content' -> 'Assets'.
2. Upload the relevant file.
3. Edit the appropriate page content/snippets for `<div>`, `<link>` or `<script>` tags. For example: `<script type="text/javascript" src='<r:assets:url title="jquery"/>'></script>`. Notice that we used another Radius macro, `<r:assets:url>`, which renders the URL of the uploaded asset.

The only difference between the two methods is how you edit the file. In-line CSS/Javascript requires you to edit each page containing such code, while using an asset allows you to quickly replace a single asset file, bringing the change to all page contents/snippets that incorporate the asset. 

Further reading

This tutorial only shows a tiny portion of what Radiant CMS can do. For more information on Radiant, visit the website at <http://radiantcms.org/>. I recommend you browse through the 'Available Tags' for more Radius macros and extensions to suit your needs. The list of extensions is available at <http://ext.radiantcms.org/>

By: Takayuki Horimoto

The author is a free software enthusiast, and founder of the University of Tsukuba Linux User Group (TsukuLUG). His website is at <http://www.opentaka.org/>.