

4. Finally, reboot the system:

```
# reboot
```

—Adarsh, addi_adarsh@yahoo.co.in



How to remove a PDF file password

'pdftk' is a handy tool to manipulate a PDF file. Install the 'pdftk' package as follows:

```
$ sudo apt-get install pdftk
```

Decrypt a PDF called 'input.pdf' by using your existing password as mentioned below. Assume that 'YOURPASSWORD-HERE' in the command below is the existing password of your PDF:

```
pdftk input.pdf output output.pdf user_pw YOURPASSWORD-HERE
```

```
input_pw password : Input PDF owner passwords
```

```
user_pw password : Input PDF user passwords
```

```
owner_pw password : Input PDF owner passwords same as input_pw
```

—Manikandan, manikandan_vs@yahoo.com



Limit bandwidth usage with apt-get

Now, you can limit the usage of Internet bandwidth with the application called apt-get.

```
$ sudo apt-get -o Acquire::http::Dl-Limit=30 upgrade
```

In the above example, the command will limit the bandwidth usage to 30KBps.

It should work for most apt-get actions (viz., *install*, *update*, *upgrade*, *dist-upgrade*, etc).

—Remin Raphael, remin@smartgeek.in



How to shift a running job to work in the background

You're running a job at the terminal prompt, and it's taking a very long time to complete. So if you want to run this job in the background, you can do so by issuing the following command:

```
"CTL - z" Temporarily suspends the job
```

```
$ jobs This will list all the jobs
```

```
$ bg %jobnumber (bg %1) To run in the background
```

```
$ fg %jobnumber To bring back in the foreground
```

Now, if you're using several suspended Emacs sessions and want all of these sessions to terminate, you can make

this happen using the command below:

```
$ kill -9 `jobs -p`
```

The 'jobs -p' gives the process number of each job, and then 'kill -9' kills or terminates all suspended sessions.

—Bhajan Lal, bhajan.lal@fiserv.com



Port listing

To get the list of all ports, type in the following command:

```
$ cat /etc/services
```

If you want to get the port number related to 'http', type in...

```
$ cat /etc/services | grep http
```

It will print all 'tcp/udp' port numbers of 'http'.

—Vikash Kumar Jha, v4evervikash@gmail.com



Add sudo to your last Bash command

While you have a couple of options for adding 'sudo' to the last command, the easiest one is to just use '!!' to instruct Bash to use the last typed command.

For instance, if you type the command given below, you will get an error stating that you are editing a read-only file:

```
$ vi /etc/apt/sources.list
```

Once that happens, you can use the following command:

```
$sudo !!
```

Bash will then expand into this command:

```
$sudo vi /etc/apt/sources.list
```

Password:

—Sandeep Verma, sandeep201187@gmail.com

END ▾ 3

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweeking. Submit them at www.linuxforu.com. The sender of each published tip will get an LFY T-shirt.