

```
# fields for username, password, remember_me
<% end %>
```

Next, wire up the routes:

```
# config/routes.rb
map.resource :user_session
map.root :controller => "events_controller", :action => "index"
```

You then need to add some code to the *Application Controller* for persisting the session.

Declare the helper methods *current_user_session* and *current_user*, which can be used in other controllers where the session object or the current user object is required:

```
# app/controllers/application.rb
helper_method :current_user_session, :current_user
```

We don't want the password to be written to the log files!

```
# app/controllers/application.rb
filter_parameter_logging :password
```

Besides the helper methods, you need to add two authentication methods to the *Application Controller*:

- *require_user*: to be used in controller actions that require signed-in users
- *require_no_user*: to be used in controller actions that require non-signed-in users

```
# app/controllers/application.rb
# current_user_session (for retrieving the current session)
return @current_user_session if defined?(@current_user_session)
@current_user_session = UserSession.find

# current_user (for retrieving the current user)
return @current_user if defined?(@current_user)
@current_user = current_user_session && current_user_session.user

# require_user
unless current_user
  flash[:notice] = "Please sign in to access this page"
  redirect_to root_url
  return false
end

# require_no_user
# check if it is the current_user
```

That's it! You are ready to use authentication in the application now! Next, ensure that only signed-in users can

create new events. Add the following code to the start of the new method in the *Events Controller*:

```
# events/app/controllers/events_controller.rb
# new

if current_user.nil?
  flash[:notice] = "You must be logged in to access this page"
  redirect_to (new_user_session_url)
  return
end
```

Try to create a new event without signing in—it should take you to the sign-in page, */user_sessions/new*. For sign-out, use: */user_sessions/destroy*.

Read more about Authlogic at <https://github.com/binarylogic/authlogic>.

Omniauth plug-in

Omniauth is a Rails plug-in that enables external authentication for your application. It allows people to use Facebook Connect. Some other supported external providers are Twitter and Foursquare via OAuth, Google Apps via OpenID and Flickr.

Installation

Install the plugin from the repository at github:

```
script/plugin install git://github.com/intridea/omniauth.git
```

Adding Facebook authentication to the Events application

For Rails v2.3.8, you need to create an initialiser for Omniauth, and specify a strategy for each external provider:

```
# events/config/initializers/omniauth.rb
#Facebook
ActionController::Dispatcher.middleware.use
OmniAuth::Strategies::Facebook, '<APP_ID>', '<APP_SECRET>'
```

Please note that you have to register your app with Facebook in order to get the API key. Also, you need to ensure that you provided the correct settings for your Facebook App:

```
Site URL = http://yoursitename.com
Site Domain = yoursitename.com
```

Next, add a 'Connect with Facebook' button to the home page (you can get the Facebook button image from the Facebook Developers website):

```
# app/views/events/index.html.erb
<a href="/auth/facebook"></a>
```