



KNOW HOW?



Q We have installed Drupal 6.x on our college's Web server and run a website on it. This installation is on Fedora with PHP 5.2, Apache 2 and MySQL 5. Now, we need to run a few more websites on the same server. Please let us know if this is possible with Drupal or do we need to set up another installation?

—Mukund Sharma,
Habib Ganj

It is definitely possible to run a single installation of Drupal to host multiple sites on the same server. This option has many benefits compared to multiple Drupal installations, the foremost being the time and effort saved in managing and upgrading each Drupal installation. The steps that you need to follow to create a new site, using a shared Drupal code base, are mentioned below:

1. Create subdirectories for the new sites that you need to host. This should be done in the directory 'sites'. For example 'website1.com', 'website2.com', 'website3.com' and so on.
2. Copy the file 'sites/default/settings.php' into the newly created subdirectory that you have created above. Rename the new file 'settings.php'.
3. Now, copy the directory 'themes' and 'modules' from 'sites/default/' to the newly created subdirectory (website1.com, website2.com, website3.com...).
4. Set permissions for the new

site directory, and allow write permissions on the configuration file.

5. Create a new database for the respective sites.
6. Finally, go to the Web browser and open the URL of the new site. From here, you can continue with the standard Drupal installation procedure.

You can get more information on how to run multiple sites on a single Drupal installation at www.drupal.org

Q I have installed CentOS 5.2 on one of my servers and it worked fine till I recently noticed a problem with it. The system is utilising the 'swap' memory, optimally. After a little time spent on diagnosis I found that the process responsible for such high resource usage was 'setroubleshootd'. Please let me know what 'setroubleshootd' is and why its resource usage is so high?

—Shweta Gupta, Nasik

'setroubleshootd' or SE Trouble Shooter is a service related to SELinux, which is responsible for notifying users about the problems that can occur due to the security contexts of files. You can check the 'sealert' and see if you have got any alerts with very high counts. Try resolving these alerts and see if the resource usage goes down.

Q I am a radiologist living in South Gujarat. I have been an avid Linux user for the last 10 years. Presently, I have an AMD X2 desktop on which I dual booted Fedora 14 and OpenSuse11.4—thanks to the DVDs provided by LFY.

Recently, I got interested in the PacsOne Server. I downloaded it and tried to install it on both my distros. Installing and configuring it was a breeze to an extent, but I got stuck after a point. I know that PacsOne Server requires PHP5, Apache 2 and MySQL database to work seamlessly with each other. Hence, I checked and found that the MySQL database is working fine. But somehow I am not getting 'httpd' to show 'hello' on `http://localhost` or `http://127.0.0.1`. Can you please help me to resolve this problem? Thanks in advance.

—Dr Darshan D Tandel,
Gujarat

Please check whether the 'httpd' service is running or not. If not, then first start the service. I assume that you have installed Apache 2 on your server. If not, then do first install Apache using YUM on Fedora 14, using the following command:

```
#yum install httpd
```

...and start it by using the command given below:

```
#/etc/init.d/httpd start or service httpd start
```

You can even download the source from <http://httpd.apache.org/download.cgi> and compile it on your system. Although this is not as easy as using YUM, yet it is recommended.

I would also suggest that you make the necessary changes while compiling Apache as mentioned in the PacsOne Server Installation Guide. Follow the instructions given in the guide to start 'httpd'. Now, check 'http://localhost'. It should work. **END** 