



TIPS & TRICKS

Allow Ctrl-Alt-Del to shutdown your system

 On an x86 system, to allow the 'Ctrl-Alt-Delete' command to shut down the system, use the entry in '/etc/inittab', which is given below:

```
# Trap CTRL-ALT-DELETE
ca::ctrlaltdel:/sbin/shutdown -t3 -r now
```

Comment it out and reboot the system or 'killall -HUP init' to activate the change.

—Narendra Gupta,
narendra.jnu07@gmail.com

Download YouTube videos through the terminal

 You can download YouTube videos directly through your command line with the help of 'youtube-dl', a neat program which downloads videos in the '.flv' format.

These video files can be played on VLC.

The program can also be installed in Ubuntu-like systems, with the following command, as the root user:

```
#apt-get install youtube-dl
```

You can use this program with the following syntax:

```
youtube-dl <url>
```

For example, if you want to download and save a file named 'foo', the command will be as follows:

```
youtube-dl "http://www.youtube.com/watch?v=foo"
```

The video file will get saved as 'foo.flv'

You can also resume the download later by using an option '-c' after 'youtube-dl' as shown below:

```
youtube-dl -c "http://www.youtube.com/watch?v=foo"
```

This way, you can pause any download and resume it later.

Watch the video download and then open it in the VLC media player and enjoy!

—Anirudh S,
anirudh24seven@gmail.com

Send your IP information to your email

 To log in to a remote computer, you will need to know its IP address. On a broadband connection, the IP address is usually a dynamic IP address, which keeps changing. So, you will need to find out your IP, every time you want to log in to your remote system.

The easiest way to do this is to send yourself an email that has your new IP information, so that you stay updated every time it changes. Let's see how you can do this.

Let us suppose you are using an xDSL connection and your system has assigned an IP address to the 'ppp0' connection.

Here are the steps to send your IP details via an email to your email ID.

- 1) Set an alias for a user (in the example below, it is 'root'). To do this, you will need to write an alias for 'root', using the following command:

```
#vi /etc/aliases
```

Now, go to the end of file and type the following command:

```
root: test@gmail.com
```

The above line will redirect emails sent to 'root' to the test@gmail.com account.

- 2) The next thing you have to do is to run the following scheduler:

```
#crontab -e
```

Now, at the following text to the crontab:

```
*/10 * * * */sbin/ifconfig ppp0|grep "inet addr"|cut -d:
```