

```
-f2|cut -d" " -f1|mail -s "IP Address" root
```

This will send the IP address information of the 'ppp0(xDSL)' adapter to test@gmail.com every 10 minutes, with 'IP Address' as the subject of the email.

This will enable you to stay updated with your frequently changing IP address details.

—Chaitanya CVHBSK,
cvhbsk@yahoo.com

A common display message on every terminal



To send and display a similar message on every terminal that is open, you can use the 'wall' command. Here is a simple example to illustrate how to do this:

```
#wall
```

```
Hi everybody
```

```
<CTRL-@>
```

```
#
```

This will display the message 'Hi everybody' on every terminal, when its user is logged in.

—Dange Laxmikant,
dange.laxmikant@gmail.com

Encrypting a text file in VI editor



To encrypt any file in the VI editor, type the following command in the command mode and press 'Enter'.

```
:X
```

You will be asked to enter a password twice, which will be used to encrypt the file. The file is now saved in an encrypted format. When opening that file, the password needs to be re-entered.

However, if you have encrypted a file containing a programming language's source code, the file cannot be compiled.

—S.Sathyanarayanan,
sathyanarayanan_s@yahoo.com

Checking 3D support for your computer

Here is a simple method to check if your laptop or desktop supports 3D acceleration or graphics.

To check this, you need to run the tool 'glxgears'.

To run the tool, open the terminal, type the following command and then press 'Enter'.

```
#glxgears
```

The output of the above command will be a picture with three gears displayed on the desktop.

Now, wait for 10 to 12 seconds. In the background, some information will appear. Now, check the FPS (frame per second) value. If the FPS is greater than 1000, it indicates your system supports 3D acceleration and graphics.

—Prem Chand Yadav,
pcy@sify.com

How to list the contents of '.jar' files, and unpack them



To list the contents of '.jar' files, type:

```
jar -tvf filename.jar
```

To unpack a '.jar' file, use the command given below:

```
jar -xvf filename.jar
```

This tip is very helpful for Java developers.

—Bhajan Lal,
bhajan.verma@gmail.com

Keeping files in two computers, in sync



Imagine a scenario where there is a remote computer with the IP address '192.168.2.11', and an account 'abc'. Now, if you want to sync the files under '/home/abc/backup' on the remote computer with files that exist on '/home/xyz/backup' on the local computer, type the following command:

```
rsync -Lae ssh abc@192.168.2.11:/home/abc/backup /home/xyz/  
backup
```

Here, we have used the 'rsync' command to keep files in sync. As shown here, the command will work through 'ssh'. The '-L' option tells 'rsync' to treat symbolic links like ordinary files.

I would suggest you go through the manual pages of 'rsync' to know more about it.

—Bhajan Lal,
bhajan.verma@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get an LFY T-shirt.