



Figure 1: VirtualBox for Solaris/OpenSolaris/OI

```
[y,n,?] y
```

```
Installing Oracle VM VirtualBox as <SUNWvbox>
```

```
[...snip...]
```

```
Installation of <SUNWvbox> was successful.
```

File operations, and the general VirtualBox used in OI, are no different than on Linux. You can even exchange VMs created in OI with Linux, and vice-versa.

QEMU

However, some developers need to deal with platforms other than x86—for example, ARM and PowerPC. So, what's the alternative to VirtualBox? The solution is straightforward—QEMU. It can emulate x86 systems and a dozen other architectures; e.g., Linux for ARM with *qemu-system-arm*, or MacOS X with *qemu-system-ppc64*.

The build process for QEMU 0.15 requires the *gettext@0.5.11* package, as well as developer packages that contain definitions of mathematical functions. I performed the following operations:

```
root@openindiana:/home/anton# pkg info | egrep "math|gettext"
Name: developer/gnome/gettext
FMRI: pkg://openindiana.org/developer/gnome/gettext@0.5.11,5.11-0.151:20110523T143743Z
Name: system/library/math
FMRI: pkg://openindiana.org/system/library/math@0.5.11,5.11-0.151:20110523T150249Z
Name: system/library/math/header-math
FMRI: pkg://openindiana.org/system/library/math/header-math@0.5.11,5.11-0.151:20110523T150250Z
```

I was able to build QEMU 0.15 without problems.



Figure 2: QEMU 0.15 compiled on OI; VM with Ubuntu Server




Figure 3: Windows 2003 EE in QEMU 0.15

However, I have to disable GuestAgents support, mainly because QEMU 0.15 calls functions with *O_ASYNC* parameters, which isn't supported on Solaris. You could compile the previous version, 0.14, or do a quick hack on line 493 in *qemu-ga.c*, from:

```
fd = qemu_open(s->path, O_RDWR | O_NONBLOCK | O_ASYNC);
```

```
...to:
```

```
fd = qemu_open(s->path, O_RDWR | O_NONBLOCK);
```

Or, as mentioned earlier, compile it without GuestAgents support:

```
$. /configure --prefix=/opt/qemu-0.15 --disable-guest-agent
# make && make install
```

After that, you should prepare a file image for the virtual OS to install to, and run it as follows: