

This will create a file called *new.pdf*, which will have only pages 1 to 5 of *1.pdf*.

Now let us look at a more complex use of *pdftk*:

```
pdftk A=one.pdf B=two.pdf cat A1-7 B1-5 A8 output combined.pdf
```

In the above example, we have selected different pages from different PDF files and merged them into *combined.pdf*.

—Neeraj Garg,
neerajgarg1109@gmail.com

How to begin with C programming in Linux

Here is a simple tip that will enlighten newbies on how to compile their first program using C.

Make sure that you have C compiler installed before trying out the following steps. Now, create a file *abc.c* using any text editor.

Open *gedit* and enter the following code:

```
#include<stdio.h>
void main()
{
    printf("Hello world\n");
}
```

Now save it as *abc.c* in your *home/username* folder. Next, to compile this code, open the terminal and run the following command:

```
#gcc abc.c
```

On successful compilation, you will notice that a file named *a.out* has been created. This is the file you will need to run by typing the following command in the terminal:

```
./a.out
```

In case you want to give the executable file your own name rather than 'a.out', then you should compile it by using the *-o* option, as follows:

```
#gcc abc.c -o hello
```

...where *-o* stands for the output file name.

—Rajnish Kumar,
rajnishs91@gmail.com

Know the package behind the command you run

Often we need to know which command is packed with

which rpm package. So, here is a tip to find out the name of the package with the help of the 'yum' command. For this you should have the Yum server configured on your machine, locally or remotely.

Let's look at the example of the date command:

```
#yum whatprovides /bin/date
```

```
Loaded plugins: refresh-packagekit,
coreutils-8.4-9.el6.x86_64 : A set of basic GNU tools
                        : commonly used in shell scripts
```

```
Repo      : base
Matched from:
Filename   : /bin/date
```

```
coreutils-8.4-9.el6.x86_64 : A set of basic GNU tools
                        : commonly used in shell scripts
```

```
Repo      : installed
Matched from:
Other      : Provides-match: /bin/date
```

The above output provides you with the actual name of the package that is installed on your machine.

In case the package is not present on your machine, you can ask Yum to do the search work for you. For example, I can't locate the 'mutt' command on my system, so I ran the following command:

```
#yum whatprovides */mutt
```

This will list the number of packages so that you can actually get the name of the package, as follows:

```
Loaded plugins: refresh-packagekit,
```

```
5:mutt-1.5.20-2.20091214hg736b6a.el6.x86_64 : A text mode
                                                : mail user
                                                : agent
```

```
Repo      : base
Matched from:
Filename   : /usr/bin/mutt
```

—Namrata Mapgaonkar,
namrata.mapgaonkar@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get a T-shirt.