

Arch	Description
X86	Installation ISO image (x86)
X86_64	Installation ISO image (x86/64)
X86	x86 VMware Virtual Appliance
X86_64	x86/64 VMware Virtual Appliance
X86	x86 VMware ESX Virtual Appliance
X86_64	x86/64 VMware ESX Virtual Appliance

openfiler.com/community/download:

Openfiler architecture

OS: Openfiler uses the Linux 2.6 kernel base to deliver a wide-ranging storage management solution that fulfills the needs of enterprise applications.

Block devices: Physical block devices are directly attached to the Openfiler host appliance. SATA, SAS, SCSI and FC disks are some of the supported *physical block devices*. iSCSI, AOE or FCOE protocols are used to access remote block devices, which are defined as *virtual block devices*.

Dynamic volume aggregation and software RAID and replication layers: These are abstraction layers over block devices, and they make no distinction between physical block devices and virtual block devices. A storage pool of virtual block devices, RAID volumes and replicated volumes is created of all the raw block storage before storage is presented to the export layers. Dynamic volume aggregation can be used to create point-in-time snapshots of volumes as part of a backup strategy. Openfiler support for synchronous and asynchronous block-level replication is useful in creating disaster-recovery solutions. Openfiler supports RAID 0, RAID 1, RAID 5, RAID 6 and RAID 10.

Logical volumes and PITC volumes: Openfiler allows the administrator to allocate partitions (logical volumes) of a Dynamic Volume Aggregation (DVA) instance, which can then be presented to clients over supported storage networking protocols. A PITC (Point in Time Copy volume) is an image of a logical volume. One logical volume can have one or more PITC volumes.

File systems: Openfiler supports on-disk file systems such as XFS, ext3, ReiserFS v3 and JFS. XFS and ext3 are file systems that enhance data security and reduce the need for regular file system checks. File level protocols are covered over a file system, while block level protocols feed directly over logical volumes.

Main features of Openfiler

Hardware requirements

Openfiler has the following hardware requirements that need to be successfully installed: an x86 or x64-based computer with at least a 64-bit processor with 1.6 GHz or more, 512 MB RAM, a CD ROM or DVD-ROM drive if you are performing a local install, and 10 GB hard disk space (8 GB for OS installation and 2 GB for swap space).




Figure 1: Openfiler architecture (Source: Openfiler)




Figure 2: Features (Source: <http://www.openfiler.com/prod/>)



Figure 3: Openfiler installation

For a bare metal installation, you will need a 64-bit 1.6 GHz or higher performance processor, 2 GB disk space for memory swap area, 8 GB disk space for Openfiler OS