

cbrowser-0.8 is a directory and the files in this directory are listed below it. You can select the file and press *Enter* to open them in VIM.

—Rahul Bedarkar,
rahulbedarkar89@gmail.com



Back up and restore permissions of directories

To back up permissions of a directory, use the *getfacl* command. *getfacl* gets file access control lists. Here, you will get the *acl* and store it in a file as shown below:

```
getfacl -R <Directory Name> > permissions.acl
```

Change the permissions as you wish and when it's time to restore the permissions, you can easily get back to the original permissions by using the following command:

```
setfacl --restore=permissions.acl
```

—Vinit Khandagle,
vinit.khandagle@gmail.com



Efficient browsing of source code using vim-taglist

Taglist gives an overview of the structure of the source file and allows you to jump to a particular function of a source code. This makes navigation through a source file easy and efficient.

Installation: Download the plugin *taglist.zip* from <http://sourceforge.net/projects/vim-taglist/files/> and unzip the files in *\$HOME/.vim*. This will create two files:

```
plugin/taglist.vim - main taglist plugin file
doc/taglist.txt    - documentation (help) file
```

Now restart the *vim* and open any source file (*hello.c*). If you run the following command:

```
:TlistOpen
```

...you should see the *taglist* window. You can navigate to any particular index on the *taglist* just by pressing *Enter*. The *taglist* plug-in requires *ctags* to operate. Make sure you have *ctags* before using the *taglist*. You can open the tag in a new horizontal window by pressing 'o' instead of the *Enter* key.

Here is an example of *.vimrc* configuration for a *taglist* plug-in:

```
let Tlist_Auto_Open = 1          //
Opens the taglist whenever i open vim
```

```
let Tlist_Use_Right_Window = 1    // Put the
taglist window on the right side of the screen.
set mouse=a                       //
Enable mouse mode for cursor movement. Navigation becomes
easier if the mouse movements are enabled.
set selectmode=mouse              // You
can copy text by using mouse. This is Visual mode of
operation in vim
let Tlist_Ctags='/usr/local/bin/ctags/' // Gives
the location of ctags. Remember, for taglist to work you
need ctags.
map <C-C> "+y<CR>                 // This
is used to copy the text selected from mouse movements.
Read Notes for additional information.
map <A-Right> :TlistOpen<CR>      // Mapping
'Alt + RightArrow' keystrokes for opening taglist window.
map <A-Left> :TlistToggle<CR>    // Mapping
'Alt + LeftArrow' keystrokes for opening/closing taglist
window.
let Tlist_Use_SingleClick = 1     // A
single click in the taglist window will take you to that
tag.
let Tlist_Exit_OnlyWindow = 1    // When you
exit vim, taglist also will be closed.
```



- Note:** 1. To enable copying in Visual mode from Vim to a different application, you need to have a Vim version in which system-wide clipboard is supported. A system-wide clipboard is available if you see *+xterm_clipboard* when you run *:version* in the command mode of Vim. While running Vim, if you see *-xterm_clipboard*, then install Vim from source by providing *xterm_clipboard* in the configuration file as an additional option.
2. If you are using *screen*, you need to change the key bindings, as *Alt + Right/Left Arrow* is bound to some other function in *screen*.
 3. Mouse movements are not possible if you are using *ssh* to a remote machine running Vim.

Hope this information will be useful for you.

—Shashidhar G,
gshashidhar125@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in OSFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get a T-shirt.