

```

        Your browser doesn't support HTML5 video.
</video>
<br/>
<button id="btn_play" onclick="play_vid()">Play</
button>
</body>
</html>

```

It is self-explanatory for those who know JavaScript. For those who don't, the explanation is as follows. We created a video element with no controls and set its ID as *vid*. A button is created and its *onclick* event is mapped to the JS function *play_vid*, which means the function *play_vid* will be executed when the button is pressed. The JS function just creates a variable *vid*, stores the *vid* element to it and calls it *play* method. The video plays. Other controls like *pause* and *stop* are left to you. Make use of the mentioned references.

<audio> Element

<audio> is almost similar to <video>. A notable difference is that you don't have to give the width and height. Here is an example:

```

<audio controls>
  <source src="file.ogg" type="audio/ogg">
  <source src="file.mp3" type="audio/mpeg">
  Your browser doesn't support HTML5 audio.
</audio>

```

Animation using CSS3

Creating animations using CSS3 is interesting. The best part is that any HTML element can be animated – paragraphs, images or buttons; basically, anything you would like to can be animated. Standard SVG (vector) images can also be animated using CSS3.

Some merits of CSS3 animation are:

- Animations are rendered in the user's device. The downloading of large-sized animated files can be avoided. This decreases the delays during page loading.
- Being rendered in the user's device, animations will be suitable for the resolution of that device.
- Does not need the installation of any additional plug-ins.

Like any other stylesheet item, CSS3 animations can also be defined inside the HTML file or included in an external stylesheet file. We will go through some examples to learn more about CSS3 animation. Since the HTML part is small, we will merge both HTML and CSS elements in a single HTML file. Once you get the basics of animation, you can cut and paste the stylesheet part to an external CSS file.

Technique

The technique is simple. We can use the same *class=* or *id=* method to assign animated styles to objects. In the definitions of the style, we should apply *animation: anim_defn*,

where *anim_defn* is defined outside the style as *@keyframes anim_defn*. The body of *@keyframes* contains the details (i.e., keyframe descriptions) about the animation. The following examples will make things clear.

Method 1: The *from-to* method

This is the simplest way to animate things. You give the commands *from* (*INITIAL STYLE OF THE OBJECT*) and to (*FINAL STYLE OF THE OBJECT*). *STYLE* can be any style code that you give in normal CSS. To learn the basics, we use *colour*: here.

Consider this example:

```

<!DOCTYPE HTML>
<html>
  <head>
    <meta charset="utf-8"/>
    <title>CSS3 Animation</title>

    <style>
      .style_anim
      {
        animation: anim_kf 5s;
      }

      @keyframes anim_kf
      {
        from {color:black;}
        to {color:green;}
      }
    </style>
  </head>

  <body>
    <h1 class="style_anim">Hello</h1>
  </body>
</html>

```

When the page is loaded in a Web browser, a heading-like text *Hello* changes its colour from black to green within five seconds. Some browsers won't support the above code. Before going into that issue, let us explore this piece of code.

The body contains only one element with an *<h1>* tag. It is the text *Hello*. We assign a style *style_anim* to it. Its definition is given in the head. The style contains a line beginning with *animation:* which points to the *@keyframes* rule of the animation. The following element is the duration of the animation—in this case, five seconds. The *@keyframes* rule contains the initial and final states of the style, given after *from:* and *to:*. The *from* style has black as its colour and the *to* style has green. It means our text *Hello* should be black at the beginning of the animation clip and green at the end of the animation. How very simple!

Some older browsers do not support the above code. All the latest browsers support CSS animation, but we have to consider those that use older browsers also. The problem