



Encrypt an image using the command line

First, get a PNG image file and run the following command:

```
$echo p4ssw0rd|convert vizay.png -encipher - hidden.png
```

...where *p4ssw0rd* is our secret key for encryption and *hidden.png* is the encrypted image.

Now, to confirm the encryption, check whether or not the image can be seen as earlier by running the following command:

```
$display hidden.png
```

This should display the scrambled image and not the actual one if everything is fine.

Now, let's decrypt the image by running the following command:

```
$echo p4ssw0rd|convert hidden.png -decipher - new.png
```

Here *new.png* is our decrypted image.

Running the command below will display the original image:

```
$display new.png
```

The *new.png* will be same as the original image, vizay.png

—Vizay Soni,
vs4vijay@googlemail.com



Back-up and restore Thunderbird e-mails

In Linux, when you want to reinstall your system for any reason, you need to take a back-up of your data along with your e-mails in Thunderbird. Given below are a few simple steps that let you take a back-up of e-mails manually.

1. Check for your Thunderbird e-mail and profile folder. If you have not changed it, it should be at `/home/<username>/thunderbird/<alphanumeric_named>.default_folder/`

For example, the alphanumeric folder name on my system is *vx3vg9j2.default*

2. Copy the whole alphanumeric folder and place it in some other computer or storage device as an e-mail backup. Do remember to close Thunderbird before doing this.
3. After reinstalling your PC with any Linux-based OS, install the Thunderbird e-mail client and configure your e-mail credentials before closing the Thunderbird client.
4. Go to your Thunderbird folder in the new installation `/home/<username>/thunderbird/<alphanumeric_named>` folder. The alphanumeric named folder will be a different one now.

For example: `/home/guest/thunderbird/jx3gv9k2.default`

5. Copy the contents of the old alphanumeric folder that is kept as a backup to the above location.

That is, you need to copy the contents of *vx3vg9j2.default* to *jx3gv9k2.default*

6. Now, open the Thunderbird client and you will find that all the e-mail credentials, e-mails, e-mail rules and address book will be available as they were before re-installation.

—Sobhanadri Agnihotram,
sobhanadri.a@gmail.com



Execute commands on a remote Linux machine

If you want to execute any command or script on a remote Linux machine, you can use *ssh*. Shown below are a few examples.

The syntax for running a command or script on a remote server is: