

```

title></head>
11 <body>

12 <sql:query var="dept_names" dataSource="jdbc/MainPool_
Level_1">
13   select dpt.id, dpt.title
14     from dept_structure dpt, status s
15      where dpt.id = s.id
16        and dpt.administrative_level = 1
17   order by dpt.title
18 </sql:query>

19 <select onChange="location = 'list_warehouse_products.
jsp?id=' +           this.options[this.selectedIndex].
value">
20   <option value="0">Select Department</option>

21   <c:forEach var="dept_names" items="${dept_names.rows}">
22     <option value="${dept_names.id}">${dept_names.title}</
option>
23   </c:forEach>

24 </select>

25 <%
26   idDept = request.getParameter("id");
27   if (idDept == null) {
28     idDept = 0;
29     out.println("Choose necessary department!" +
"<br>");
30   } else {
31     out.println("Department ID:" + idDept +
"<br>");
32     System.out.println("MY_REPORTS >>> Department
ID:" + idDept);
33   }
34 %>

35 <% number = 1; %>

36 <sql:query var="def_level_1" dataSource="jdbc/MainPool_
Level1">
37   select
38     ps.id as ID, ps.short_title as PS_Title,
39     dpt.title as DPT_Title, st.status as Status,
40     st.modification_date as MoDate
41   from ps_passport ps, status st, dept_structure dpt
42    where ps.id = st.id
43      and dpt.id = ps.dept_structure
44      and dpt.id = <%= idDept %>
45   order by ps.short_title, st.status
46 </sql:query>

47 <c:forEach var="row_level1" items="${def_level_1.rows}">

```

```

48 <fieldset width=100%>
49 <p width=100%>
50   <div><%= number++ %>&nbsp;&nbsp;&nbsp;ID: ${row_level1.ID}<br>
51   <i>${row_level1.PS_Title}</i><br>
52   <b>${row_level1.DPT_Title}</b><br>
53   DELIVERY DATE TO WAREHOUSE1: ${row_level1.MoDate}
   (${row_level1.Status})

54   <sql:query var="def_level_2" dataSource="jdbc/MainPool_
Level2">
55     select
56       ps.id as Level2_ID, st.status as Level2_Status,
57       st.modification_date as Level2_MoDate
58     from ps_passport ps, status st
59     where ps.id = st.id and ps.id = ${row_level1.ID}
60   </sql:query>

61   <c:forEach var="row_level2" items="${def_level_2.rows}">
62     <br>DELIVERY DATE TO WAREHOUSE2: ${row_level2.Level2_
MoDate}
63     (${row_level2.Level2_Status})
64   </c:forEach>

65   </div>
66 </fieldset>
67 </c:forEach>

68 </body>
69 </html>

```

In the above code JSP-page *list_warehouse_products.jsp* fetches, analyses and prints consolidated information from warehouses of two different levels.

In Lines 25 – 34, we process the numerical parameter *id* and convert it into a string-typed variable *idDept*. At Line 35, we initialise the counter used for displaying products in every chosen department.

Then we prepare another SQL-query, in lines 36 – 46, which is used to fetch products from this particular department. This information will be stored in the *def_level_1* array. From which (lines 47 – 67) we will form table data to be processed in two nested loops. The beginning and the end of the bigger cycle are denoted by Lines 47 and 67, and the smaller cycle is denoted by Lines 61 – 64. For this small loop, a data array named *def_level_2* (this is actual information from the parent warehouse) is formed, where product identifiers are calculated from the bigger loop.

Lines 68-69 imply that the HTML-page has reached its end.

Even though this looks a bit complicated, the whole procedure is pretty simple.

Now, let's take a look at how to declare a single data source (for example, *MainPool_Level_1*) in order to get data from PostgreSQL. Please browse to the *conf/Catalina/localhost* directory within the Tomcat