

from an Oracle 10g DBMS as plain text. If you want to use another DBMS, you can do so as long as the plain text output is similar to the one used.

The following PL/SQL listing shows the PL/SQL code that extracts the required information from an Oracle 10g DBMS:

```
REM
REM Author: Mihalis Tsoukalos
REM

set echo off
set heading off embedded off verify off
set feedback off
spool table_col.log

btitle off
ttitle off
set termout off

SELECT table_name, column_name
FROM user_tab_columns
ORDER BY table_name
/

PROMPT TABLESPACES

SELECT table_name, tablespace_name
FROM user_tables
/

spool off
```

It makes use of Oracle USER_TAB_COLUMNS and USER_TABLES tables. The Perl script used is shown in the following listing:

```
#!/usr/bin/perl -w
#

use strict;

my $tablespace_found = 0;
my $line="";

# The following two hashes will hold the
# names of the tables and the tablespaces.
my %TABLE = ();
my %TABLESPACE = ();

my $firsttable = 1;

die <<Thanatos unless @ARGV;
usage:

$0 inputfile.log outputfilename
```

```
inputfile.log: The input filename
outputfilename: The filename of the output
Thanatos
```

```
if ( @ARGV != 2 )
{
    die <<Thanatos
    usage info:
        Please use exactly 2 arguments!
Thanatos
}

my $input = $ARGV[0];
open(INPUT, "< $input " ) ||
    die "Cannot read $input: $!\n";

my $output = $ARGV[1].".dot";
open(OUTPUT, "> $output " ) ||
    die "Cannot write $output: $!\n";

print OUTPUT "digraph G\n";
print OUTPUT "{\n";
print OUTPUT "\tgraph [rankdir = \"LR\"]\n";
print OUTPUT "\tnode[fontsize = \"14\" style=bold]\n";
print OUTPUT "\n\n";
print OUTPUT "\n# Table-field connection part.\n";

# Read the input file
while ($line = <INPUT>)
{
    chomp $line;
    # Drop empty lines
    if ( $line =~ /^$/ )
    {
        next;
    }
    if ( $line =~ /^TABLESPACE/ )
    {
        # Close the previous table node.
        print OUTPUT " \"\n\tshape = \"record\"\n\t]\n";
        print OUTPUT "\n# TABLESPACE-table connection
part.\n";
        $tablespace_found = 1;
        next;
    }
    if ( $tablespace_found )
    {
        my $tablespace = (split " ", $line)[1];
        my $table = (split " ", $line)[0];
        # Connect tables with their Tablespaces
        print OUTPUT "\t$table:tb -> TB_{$tablespace}:tb\n";
        if ( !defined $TABLESPACE{$tablespace} )
        {
```