

which is designed primarily for tablet computers. The A13 does not have HDMI or SATA connections.

- **Intel Medfield (X86):** Medfield SoCs are built with 32nm HKMG technology, and are based on x86 technology. They offer OEMs a 1.6 – 2 GHz single-core processor and PowerVR's SGX540 GPU. Some devices that use the Intel Medfield SoC are the Orange San Diego (Santa Clara), the Lenovo K800 and the Lava Xolo X900.

## Deciding device configuration

All the next generation Android tablets and smartphones available pack in one of the SoCs mentioned above. Sure, every SoC manufacturer will promote its own brand with terms like, 'power efficiency', 'high performance', '3D graphics', 'full HD video', etc, but all these competing platforms will offer an overall enjoyable user experience, with few differences between them. The fact is that while choosing a device, you should not only consider the SoC's capabilities, but also other factors like display technology, wireless connectivity, camera performance and storage.

Whatever be the current system requirements, the hardware and Android version should always be chosen keeping in view the future requirements of the target system.

Let us return to the AGROSTAR company's

requirements. On examining the complete system requirements, we concluded that we would need a good hardware configuration that has high-definition audio and video capabilities, as well as Bluetooth and Wi-Fi for communication. On exploring the current crop of SoCs and the tablet market, an existing tablet model supporting Android version 4.1 with an AllWinner SoC was found suitable for the prospect's requirements and budget.

To conclude, the existing models in the market might suit an enterprise's need, and in most cases, will prove to be an economical option. However, there may be specific needs like a fingerprint scanner for an attendance terminal, or a card reader for a retail billing kiosk. In such cases, there may be a need for a custom device design to ensure in-built support for the extra accessories. Integrating existing device models with third-party hardware may be considered as an alternative, depending on the deployment intricacies and budget restrictions. 

### By: Pooja Maheshwari

The author is a technical architect at Impetus Technologies. She has about 12 years of IT experience, with wide exposure in the design and development of enterprise mobility solutions, mobile device management solutions and Android-based custom device solutions for enterprises. She is currently involved in R&D and applicability of Embedded Android for enterprises in various segments.

FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK

# We Value Your Feedback

We love to hear from you  
as **OSFY** consistently  
strives to make  
its content **informative,**  
**interesting** and  
**engaging** as possible.



Please share your feedback/ thoughts/  
views via email at [osfyedit@efyindia.com](mailto:osfyedit@efyindia.com).

We welcome your comments/ suggestions and encourage you to send them to:  
The Editor, D-87/1, Okhla Industrial Area, Phase 1, New Delhi-110020.

**OpenSource**  
THE COMPLETE SOURCEBOOK ON OPEN SOURCE  
For You

FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK FEEDBACK