

Figure 1: DavMail and mail applications




Figure 2: DavMail gateway settings

add-on for the Calendar set-up) on Windows XP and Windows 7. Given below are the steps to set it up.

Download and install Mozilla Thunderbird from <http://www.mozilla.org/thunderbird/> and DavMail from <http://davmail.sourceforge.net/download.html>.

DavMail configuration

After installation, you can find DavMail running in your system tray. Right-click it and select *Settings*. In the *Main* tab, enter your Outlook Web Access URL (see Figure 2). Leave the rest as it is. Go to the *Proxy* tab and enter your proxy details if you are behind a proxy server; else, skip this.

Now, DavMail is running on our desktop itself—*localhost*. If it's installed for use as a service on a dedicated host, you'd use the IP address/hostname for that system in your email client settings—for instance, as is shown below for Thunderbird.




Figure 3: LDAP settings—part 1




Figure 4: Calendar settings



Note: We recommend you uncheck the option 'SMTP save in sent' in DavMail → *Advanced settings*. This will avoid having two copies of an email in *Sent Items*.

Thunderbird account configuration

Run Thunderbird after installation. The first run will start a wizard to create an account. Enter your name, email ID and the password given to you by your IT support team and click *Continue*. Now Thunderbird will try to auto-configure the account; just stop it by clicking the *Stop* button. You should get a plain configuration screen with some default values. Click the *Manual Setup* button and set up *localhost* as the server hostname, and the ports defined in DavMail: POP port 1110, IMAP port 1143 (for receiving email from Exchange); and