

```
#chmod o+t mydir
```

This feature is extremely useful for group projects where multiple users are using the content from one single directory.

—Tulika Narang,
n.tulika@gmail.com



Changing port of ftp and ssh

Here is a simple tip to change the default ports of ftp and ssh.

To change the port of ssh, edit the file `/etc/ssh/sshd_config` and add the following line:

```
Port 222
```

Restart the service of ssh to make the changes effective. Now you need to specify the port number using option `-p` whenever you want to access this system.

```
#ssh localhost -p 222
```

In order to change the port of ftp server, edit the file `/etc/vsftpd/vsftpd.conf`

```
listen_port=2100 ##add this line
```

Restart the service of ftp.

Now run the following command to check if the listening ports have been changed or not:

```
ftp localhost 2100
```

You can even check the open port using the `netstat` or `nmap` commands.

—Sumit Chauhan,
sumit1203@gmail.com



Creating a desktop shortcut in Ubuntu

Here is a command to create a desktop shortcut for any folder:

```
ln -s /home/test ~/Desktop/abc
```

This will create a shortcut of the folder named `test` (in `/home/test`) on the desktop, which will be named `abc`.

This can be applied to most of the Linux flavours and not only to Ubuntu.

—Shakir Memon,
shakir22cs@gmail.com



Make your pen drive bootable

If you cannot boot from the DVD/CD-ROM drive, but can boot using a USB device such as a USB pen drive, the following alternative method can be used to boot Linux.

1. Check the name of your pen drive by issuing the following command:

```
#fdisk -l
```

This will show the pen drive's name and size, e.g., `/dev/sdb`

2. Copy a file name `diskboot.img` for redhat installation dvd to root of the USB disk.
3. Take a back-up of the data on the pen drive, and then execute the following command:

```
#dd if=/root/diskboot.img of=/dev/sdb
```

4. In the BIOS, set the first Boot device as USB Device.

—Suresh Jagtap,
smjagtap@gmail.com



Log in message

Here is how to get greeted with a welcome message every time you log in. Create a shell script in your home directory as `welcome.sh`:

```
$touch welcome.sh
```

```
$chmod 777 welcome.sh
```

```
$cat welcome.sh
```

Then add the following text to `welcome.sh`:

```
sleep 10
```

```
fortune -s > record
```

```
read a < record
```

```
notify-send "$a"
```

Now add `welcome.sh` to your start-up applications and enjoy 'fortunes' every time you log in. The fortune command in Linux prints a random epigram.

—Sachin Selokar,
sachinselokar@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in OSFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get a T-shirt.