

```
data
<class 'pandas.core.frame.DataFrame'>
Int64Index: 366 entries, 0 to 365
Data columns:
EDT                366 non-null values
Max TemperatureF   366 non-null values
Mean TemperatureF  366 non-null values
Min TemperatureF   366 non-null values
Max Dew PointF     366 non-null values
MeanDew PointF     366 non-null values
Min DewpointF      366 non-null values
Max Humidity        366 non-null values
Mean Humidity       366 non-null values
Min Humidity        366 non-null values
Max Sea Level PressureIn 366 non-null values
Mean Sea Level PressureIn 366 non-null values
Min Sea Level PressureIn 366 non-null values
Max VisibilityMiles 366 non-null values
Mean VisibilityMiles 366 non-null values
Min VisibilityMiles 366 non-null values
Max Wind SpeedMPH   366 non-null values
Mean Wind SpeedMPH  366 non-null values
Max Gust SpeedMPH   365 non-null values
PrecipitationIn      366 non-null values
CloudCover           366 non-null values
Events               162 non-null values
WindDirDegrees       366 non-null values
dtypes: float64(4), int64(16), object(3)
```

As you can see, there are 366 entries in the given dataframe. You can get the column names using `data.columns`.

The output of the command is given below:

```
data.columns
Index([EDT, Max TemperatureF, Mean TemperatureF, Min
TemperatureF, Max Dew PointF, MeanDew PointF, Min DewpointF,
Max Humidity, Mean Humidity, Min Humidity, Max Sea Level
PressureIn, Mean Sea Level PressureIn, Min Sea Level
PressureIn, Max VisibilityMiles, Mean VisibilityMiles, Min
VisibilityMiles, Max Wind SpeedMPH, Mean Wind SpeedMPH,
Max Gust SpeedMPH, PrecipitationIn, CloudCover, Events,
WindDirDegrees], dtype=object)
```

To print a particular column of the dataframe, you can simply index it as `data['EDT']` for a single column or `data[['EDT','Max Humidity']]` for multiple columns. The output for `data['EDT']` is:

```
data['EDT']
0    2012-3-10
1    2012-3-11
```

```
2    2012-3-12
3    2012-3-13
4    2012-3-14
5    2012-3-15
6    2012-3-16
...
...
...
361   2013-3-6
362   2013-3-7
363   2013-3-8
364   2013-3-9
365   2013-3-10
Name: EDT, Length: 366
```

And the output for `data[['EDT','Max Humidity']]` is:

```
data[['EDT','Max Humidity']]
<class 'pandas.core.frame.DataFrame'>
Int64Index: 366 entries, 0 to 365
Data columns:
EDT                366 non-null values
Max Humidity        366 non-null values
dtypes: int64(1), object(1)
```

Sometimes, it may be useful to only view a part of the data, just so that you can get a sense of what kind of data you are dealing with. Here you can use the head and tail functions to view the start and end of your dataframe:

```
data['Max Humidity'].head()
0    74
1    78
2    90
3    93
4    93
Name: Max Humidity
```



Note: The head and tail functions take a parameter which sets the number of rows to be displayed. And can be used as `data['Max Humidity'].head(n)`, where 'n' is the number of rows. The default is 5.

Working with columns

Now that we have a basis on which to work with our dataframe, we can explore various useful functions provided by Pandas like *std* to compute the standard deviation, *mean* to compute the average value, *sum* to compute the sum of all elements in a column, etc. So if you want to compute the mean of the 'Max Humidity' column, for instance, you can use the following commands: