

```
% telnet abcdefgh.com 80
Trying 20x.xx.xxx.xxx...
Connected to abcdefgh.com.
```

Escape character is '^['.

```
get /
HTTP/1.0 302 RD
```

```
Location: http://www.abcdefgh.com/
Connection closed by foreign host.
```

The response from port 80 shows that the Web server is running.

—**Tanaji Yadav,**
tanajiyadav@hotmail.com

Know your HDD partitions

Given below are a few of the commands that will help you know more about HDD partitions on your system. Open the terminal and run the following commands.

a) mount: This will show all partitions that are currently mounted.

```
#mount -l
```

b) fdisk: This will show all partitions of your hard disk, whether they are mounted or not.

```
#fdisk -l
```

c) blkid: This shows all partitions, with their labels and UUID (Universally Unique Identifier). The UUID of the partition is a very important piece of information. It is required while editing files like */etc/fstab* or even during system recovery.

```
#blkid
```

—**Lokesh Walase,**
lokeshw24@gmail.com

Get to know your IP address using the command line

To check your IP address on your Linux box, run the following command on your terminal as the root user:

```
# curl -s http://checkip.dyndns.org
```

The output will display your current IP address.

—**Indranil Kamulkar,**
indranil@solutionsinfinity.in

Check your OS and CPU architecture

Here is a tip that will let you know your OS and CPU

architecture. Run the following command in the terminal:

```
#uname -m
```

If the response is i686 or i386, you are running a 32-bit OS.

If the response is x86_64, you have a 64-bit version OS.

To check the architecture of your CPU, run the following command:

```
#grep lm /proc/cpuinfo
```

If it gives an output consisting of the letters *lm*, it means the CPU of your machine has support for 64-bit architecture. *lm* stands for *long mode*.

—**Lokesh Walase,**
lokeshw24@gmail.com

Finding out the line numbers in Vi editor

Here are a few simple methods that will let you know the total number of lines in the file that has been opened in the Vi editor.

:= - Shows the total number of lines.

.: = - Shows the current line number.

:+ = - Shows the next line number.

:-+ - Shows the previous line number.

—**Ranjith Kumar,**
ranjith.stc@gmail.com

Deleting blank lines using grep

For those who are not familiar with *awk*, but still want a quick and easy way of removing blank lines from a flat *ascii* file, here is a combination of the *cat* and *grep* commands that will help you do so.

```
# cat file1 | grep -v '^$' > file2
```

Here, *file1* is the file with blank lines and *file2* does not have any blank line.

—**Sumedh Gajbhiye,**
sumedh.gajbhiye1985@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get a T-shirt.