

```
    return 0;
}
```

Now we have replaced all the important functions of *conio.h*. But think about the complexity of the code above—this long code snippet was the replacement of short Code !! Here arises the need to write our own *conio.h*.

Our own conio.h!

Let's combine all our techniques in our own *conio library*. To keep things simple, let's not create a .so shared library, but write *conio.c* and *conio.h* separately. Here are the codes, with some additional functions from our earlier discussion (such as *nocursor()* and *showcursor()*) also:

conio.c:

```
// conio.c for ANSI C and C++
// Extra functions are also provided.
// (C) 2013 Nandakumar <nandakumar96@gmail.com>

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include "conio.h"

// General Utility Functions

void cagxy(unsigned int x, unsigned int y) // Clear and
Goto X,Y
{
    printf("\x1b[%d;%df", CLEAR, y, x);
}

void clrscr() // Clear the Screen
{
    printf("%s", CLEAR);
}

char getch()
{
    char c;
    system("stty raw -echo");
    c=getchar();
    system("stty cooked echo");

    return c;
}

void gotox(unsigned int x)
{
    printf("\x1b[%dG", x);
}
```

```
void gotoxy(unsigned int x, unsigned int y)
{
    printf("\x1b[%d;%df", y, x);
}

void nocursor()
{
    printf("\x1b[?25l");
}

void reset_video()
{
    printf("\x1b[0m");
}

void showcursor()
{
    printf("\x1b[?25h");
}

void textcolor(char *color)
{
    printf("%s",color);
}

void textbackground(char color[11])
{
    char col[11];
    strcpy(col,color);
    col[2]='4'; // The given color will be fg color.
    Replace '3' with '4'.
    printf("%s",col);
}
```

conio.h:

```
// conio.h for ANSI C and C++
// Extra functions are also provided.
// (C) 2013 Nandakumar <nandakumar96@gmail.com>

#ifndef CONIO_H
#define CONIO_H

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

// General Utility

#define CLEAR "\x1b[2J"
#define SET11 "\x1b[1;1f" // Set the Cursor at 1,1
```