

lammpp directory. Start XAMPP with the following command:

```
/opt/lampp/lampp start
```

- Copy the TestLink tar file to the Web server location `/opt/lampp/htdocs/` as follows:

```
cp testlink-ga-testlink-code-testlink_1.9.tar.gz /opt/lampp/htdocs/
```

- Now untar TestLink using the following command:

```
tar xvfz testlink-ga-testlink-code-testlink_1.9.tar.gz
```

- You can rename the TestLink code as follows:

```
mv testlink-ga-testlink-code(old name) testlink (new name)
```

- Open '`config.inc.php`', change the location of the logs and `upload_area` as per the existing directory structure.
- TestLink needs permission to save images and write into logs; so change permissions for the following folders:

```
$ chmod 777 upload_area
$ chmod 777 logs
$ chmod 777 gui/template_c
```

- TestLink can now be accessed from the Web browser: `http://ipaddress(newname)` Example: `http://192.168.0.100/testlink`
- The welcome page will open in the browser.
- Click on 'New Installation' and agree to the terms and conditions. Proceed after validation of all the directories and paths.
- Now set the parameters for the database, and select the database as default (database login name should be 'root' with password left as blank). Test link database user name and password are created by TestLink, choose them properly and note them down for later reference. Click on 'Process test link setup'.
- Once the installation is done, you can see the link as shown in Figure 1. It can be opened in a browser and you can log in with the user name and password as `admin`.

TestLink is now installed and ready to be used as a test management tool. You will get some security warnings at the top of the screen, like, "There are security warnings for your consideration. See details on file: `/home/user/tl/logs/config_check.txt`." To disable any reference to these checks, set `$tlCfg->config_check_warning_mode = 'SILENT'`. To remove these warnings, edit the `config.inc.php` file present in the TestLink folder, and edit the line mentioned from 'FILE' to 'Silent'.

The TestLink process

Test project: The process starts with creating a test project, by first selecting some of the enhanced features specific to the test



Figure 1: Successful installation screen




Figure 2: Overall view

project, like requirement management, test priority, inventory management, enabling the test automation API and issue tracker integration. This test project can be made private and, also, once the project is completed it can be made inactive.

Test plan: During its creation, the test plan is linked with the test cases and the optional platforms on which the test cases have to be executed. The build or release creation comes next, based on which the test cases have to be executed.

Test specification: It holds the test suites which, in turn, have the actual test cases. The requirements and the test cases are added independently in the tool, and later linked with each other. While creating requirements, you can specify the number of test cases needed to test the requirement. Once test cases are created, the keyword and the requirement can be added later. The keywords are for easy filtering of the test cases.

Once you have the test cases, test plan and builds, the test cases are to be added to the test plan and assigned separately to the users. The ability to add different platforms is also one of the unique features of this tool. For instance, if the same test cases have to be executed on two platforms, Windows and