

you can use the HTML tags below to achieve the same.

```
<ul>
<li> create slides.html
<li> create a section for each slide
<li> add links and images
<li> add code snippets
</ul>
```

Bullets can be numbered using the `<ol>` tag.

Pictures: To insert pictures in the slides, use the HTML tag `<img>`

```

```

You can additionally position the picture in the centre using the CSS attributes or HTML tag `<center>`. The size of the image can also be adjusted to fit the slides by using the `img` attributes: width and height.

Fragments: If you have multiple bullets in a slide and want each bullet to appear as you click 'Next', use the 'fragment' class.

```
<section>
<h2>Web Frameworks</h2>
<p>JavaScript </p>
<ul>
  <li class="fragment">jQuery</li>
  <li class="fragment">YUI</li>
  <li class="fragment">Prototype</li>
</ul>
</section>
```

The above example of code displays a slide with heading and paragraph. The bullets get displayed one at a time on

clicking 'Next' (right-arrow).

Linking: Adding links to external sites or another slide within the presentation is done by using *anchor* HTML tags.

```
<a href="http://www.linux.org">Linux Org</a>
```

(or)

```
<a href="#/3">Jump to Slide 3</a>
```

Markdown – a simpler way than HTML coding

Reveal supports Markdown features, which is simpler than writing the cryptic HTML and CSS tags. For most common formatting and markup tags used, there is a simple text equivalent. Some examples are given in Table 1.

Special features

Reveal comes with special features that use cool Web technologies. You do not need to be an expert programmer to use these features. Just be aware and apply them.

Adding depth to slides: You may have noticed that in the first slide there are four arrows for slide navigation. The most commonly used are the right and left navigation steps. Reveal allows us to add depth to slides, by allowing `<section>` to be embedded. Typically, it is a practice to add all 'backup' slides at the end of the presentation. Backup slides could have more details of main content or content that can be used by offline reviewers. One of the limitations with traditional presentation software is that backup slides are all combined making it difficult to reference to main slide. To add context, the presenter needs to add 'links' between slides, back and forth.

Knowing the depth of the slides, you can cover the additional details in the context of the same slide.

For example, let's assume there is a presentation on open

Markdown	HTML
# Heading 1	Heading 1
## Heading 2	Heading 2
First sentence in first paragraph. Second sentence in second paragraph.	First sentence in first paragraph. Second sentence in second paragraph.
First sentence in second paragraph. Second sentence in second paragraph.	First sentence in second paragraph. Second sentence in second paragraph.
One or two blank lines after sentences is marked as paragraph.	
* Bullet 1 * Bullet 2	- Bullet 1 - Bullet 2

Table 1: Comparing Markdown and HTML code