

```
CU_ASSERT_STRING_EQUAL(actual, expected) Check actual == expected
CU_ASSERT_STRING_EQUAL_FATAL(actual, expected)
```

The automated interface dumps the output of the test results to an XML file. The following code snippet is used for the automated interface:

```
{.c}
/* Run tests using the Automated interface */
CU_automated_run_tests();
```

The compilation step is similar to the Basic example. The output is dumped to the CUnitAutomated-Results.xml file, which contains the following code:

```
<?xml version="1.0" ?>
<?xml-stylesheet type="text/xml" href="CUnit-Run.xml" ?>
<!DOCTYPE CUNIT_TEST_RUN_REPORT SYSTEM "CUnit-Run.dtd">
<CUNIT_TEST_RUN_REPORT>
  <CUNIT_HEADER/>
  <CUNIT_RESULT_LISTING>
    <CUNIT_RUN_SUITE>
      <CUNIT_RUN_SUITE_SUCCESS>
        <SUITE_NAME> Basic_Test_Suite </SUITE_NAME>
        <CUNIT_RUN_TEST_RECORD>
          <CUNIT_RUN_TEST_SUCCESS>
            <TEST_NAME> test_is_even </TEST_NAME>
          </CUNIT_RUN_TEST_SUCCESS>
        </CUNIT_RUN_TEST_RECORD>
      </CUNIT_RUN_SUITE_SUCCESS>
    </CUNIT_RUN_SUITE>
  </CUNIT_RESULT_LISTING>
  <CUNIT_RUN_SUMMARY>
    <CUNIT_RUN_SUMMARY_RECORD>
      <TYPE> Suites </TYPE>
      <TOTAL> 1 </TOTAL>
      <RUN> 1 </RUN>
      <SUCCEEDED> - NA - </SUCCEEDED>
      <FAILED> 0 </FAILED>
      <INACTIVE> 0 </INACTIVE>
    </CUNIT_RUN_SUMMARY_RECORD>
    <CUNIT_RUN_SUMMARY_RECORD>
      <TYPE> Test Cases </TYPE>
      <TOTAL> 1 </TOTAL>
      <RUN> 1 </RUN>
      <SUCCEEDED> 1 </SUCCEEDED>
      <FAILED> 0 </FAILED>
      <INACTIVE> 0 </INACTIVE>
    </CUNIT_RUN_SUMMARY_RECORD>
    <CUNIT_RUN_SUMMARY_RECORD>
      <TYPE> Assertions </TYPE>
      <TOTAL> 3 </TOTAL>
```

```
<RUN> 3 </RUN>
<SUCCEEDED> 3 </SUCCEEDED>
<FAILED> 0 </FAILED>
<INACTIVE> n/a </INACTIVE>
</CUNIT_RUN_SUMMARY_RECORD>
</CUNIT_RUN_SUMMARY>
<CUNIT_FOOTER> File Generated By Cunit v2.1-2 - Tue Jun 25
16:01:49 2013
</CUNIT_FOOTER>
</CUNIT_TEST_RUN_REPORT>
```

If you wish to specify the output XML filename, it can be set using the following command:

```
{.c}
CU_set_output_filename("Even")
CU_automated_run_tests();
```

The above XML output is dumped to an 'Even-Results.xml' file. The Basic and automated interfaces are non-interactive modes to run the tests. The interactive console mode of running tests can be initiated by using the following command:

```
{.c}
/* Run tests in interactive Console mode */
CU_console_run_tests();
```

On compilation and execution, the following menu is shown in the terminal:

```
{.bash}
$ ./console

Cunit - A Unit testing framework for C - Version 2.1-2
http://cunit.sourceforge.net/

***** CUNIT CONSOLE - MAIN MENU*****
(R)un (S)elect (L)ist (A)ctivate (F)ailures (O)ptions
(H)elp (Q)uit Enter command:
```

This allows you to run all the test suites, or select a suite to be executed. You can list all the registered suites, and also select one to modify it. You can activate or deactivate a suite and can view any failures from the previous test run. The other interactive 'Curses' mode can be invoked using:

```
{.c}
/* Run tests in interactive Curses mode */
CU_curses_run_tests();
```

A screenshot of the Curses interface is shown in Figure 1.