

```

CUnit - A unit testing framework for C - Version 2.1-2
http://cunit.sourceforge.net/

Suite Basic_Test_Suite, Test test_is_even had failures:
  1. error-fail.c:17 - CU_ASSERT_TRUE_FATAL(is_even(4) == 0)

Run Summary:
  Type      Total  Ran  Passed  Failed  Inactive
  suites     1      1    n/a      0       0
  tests      1      1      0      1       0
  asserts    3      3      2      1     n/a

Elapsed time = 0.000 seconds

```

Figure 1: CUnit-curses

Let's suppose you have the following code snippet where the third assert fails:

```

{.c}
void
test_is_even (void)
{
    CU_ASSERT(is_even(1) == 0);
    CU_ASSERT(is_even(2) == 1);
    CU_ASSERT(is_even(4) == 0);
    CU_ASSERT(is_even(3) == 0);
}

```

On executing the above, you will get:

```

{.bash}
$ ./error

CUnit - A unit testing framework for C - Version 2.1-2
http://cunit.sourceforge.net/

Suite Basic_Test_Suite, Test test_is_even had failures:
  1. error.c:17 - is_even(4) == 0

Run Summary:
  Type      Total  Ran  Passed  Failed  Inactive
  suites     1      1    n/a      0       0
  tests      1      1      0      1       0
  asserts    4      4      3      1     n/a

Elapsed time = 0.000 seconds

```

If you wish to terminate the execution of the test when an error occurs, you can use the code shown below:

```

{.c}

void
test_is_even (void)

```

```

{
    CU_ASSERT(is_even(1) == 0);
    CU_ASSERT(is_even(2) == 1);
    CU_ASSERT_TRUE_FATAL(is_even(4) == 0);
    CU_ASSERT(is_even(3) == 0);
}

int
main (void)
{
    CU_set_error_action(CUEA_FAIL);
}

```

The corresponding output is shown below:

```

{.bash}
./error-fail

CUnit - A unit testing framework for C - Version 2.1-2
http://cunit.sourceforge.net/

Suite Basic_Test_Suite, Test test_is_even had failures:
  1. error-fail.c:17 - CU_ASSERT_TRUE_FATAL(is_even(4) == 0)

Run Summary:
  Type      Total  Ran  Passed  Failed  Inactive
  suites     1      1    n/a      0       0
  tests      1      1      0      1       0
  asserts    3      3      2      1     n/a

Elapsed time = 0.000 seconds

```

The test execution stopped after the third assert failed. The different options for error actions are:

Error value	Meaning
CUEA_IGNORE	Continue on error
CUEA_FAIL	Stop on error
CUEA_ABORT	Call exit() on error

You can refer to the CUnit Programmers Guide and API documentation to know more about CUnit. 

References

- Cunit: <http://cunit.sourceforge.net/>

By: Shakthi Kannan

The author is a free software developer at the Fedora project, and also a blogger. He co-maintains the Fedora Electronic Lab project.