

```
3.5355
3.5355

octave:6> roots(C3)
ans =

5.8378 + 0.52061i
5.8378 - 0.52061i

octave:7>
```

The corresponding y co-ordinate is obtained by substituting the value of x in the corresponding line equations.

For L1, there are two different roots—4.68 and 3, implying two points of intersection (4.68, 1.76) and (3, 4).

For L2, there are two identical roots of 3.5355, i.e., $5/\sqrt{2}$, implying just one point of intersection ($5/\sqrt{2}$, $5/\sqrt{2}$).

For L3, the roots are complex, implying that there is no point of intersection in the real world.

Continued from page no 67...




Figure 1: iRedMail installation




Figure 2: Roundcube mail login

of the process, you'll be asked to reboot the system. So just issue the 'init 6' command and restart your machine. After that you can access your Roundcube mail @ <https://www.yourservername/mail> and your Admin panel @ <https://www.yourservername/iredadmin>.

Now log in to your admin panel with the username postmaster @ your virtual domain name and the password

Solve it

Finally, here's one for your grey matter. Find out the two square roots and the three cube roots of the imaginary number, i.

If you think you have got the Octave code to solve the above problem, you may email the solution to me at the email ID mentioned below. As we move on, we will have more fun with polynomials. **END** 

By: Anil Kumar Pugalia

The author, who is a gold medallist from the Indian Institute of Science, is a hobbyist in open source hardware and software, with a passion for mathematics. His exploration of mathematics, in every aspect of life, dates back to the 1990s. Mathematics and knowledge sharing are two of his many passions. Apart from that, he experiments with Linux and embedded systems to share his learning through his weekend workshops. Learn more about him and his experiments at <http://sysplay.in>. He can be reached at email@sarika-pugs.com.



Figure 3: Admin panel login

you've given during the installation process. Then create another user by clicking on the 'Add' tab and selecting 'User'. Just give the necessary details and another user will be created. Now log in with that user account and send a test mail to the postmaster user. If you receive the mail successfully, then your mail server is functioning properly.

The following services used by iRedMail may need to be restarted at some point of time: *rsyslog*, *apache2*, *postfix*, *mysql*, *slapd*, *postfix-policyd*, *dovecot*, *amavis*, *clamav-daemon*, *clamav-freshclam*, *cron*, *iredapd* and *iptables*.

So that was a quick introduction to a powerful mail server script you can use with ease. Deploy it, configure it and test it, and discover all its benefits yourself. **END** 

By: Vinayak Pandey

The author is a Red Hat Certified Engineer on RHIEL6, currently working as a teradata administrator. He spends his leisure time exploring open source tools and technologies.