

```

#define EISDIR      21      /* Is a directory */
#define EINVAL      22      /* Invalid argument */
#define ENFILE      23      /* File table overflow */
#define EMFILE      24      /* Too many open files */
#define ENOTTY      25      /* Not a typewriter */
#define ETXTBSY     26      /* Text file busy */
#define EFBIG       27      /* File too large */
#define ENOSPC      28      /* No space left on device */
#define EPIPE       29      /* Illegal seek */
#define EROFS       30      /* Read-only file system */
#define EMLINK      31      /* Too many links */
#define EPIPE       32      /* Broken pipe */
#define EDOM 33 /* Math argument out of domain of func */
#define ERANGE 34 /* Math result not representable */
#endif

```

With this, I conclude the first article in the two-part series. We have discussed the system call execution model from the user mode perspective as well as the

role of the C library wrapper function in system call execution. We now understand how C library loads system call arguments into architecture-specific registers and generates *syscall* interrupt to switch the mode from user space to kernel space.

In the next and final part we will discuss system call execution from the perspective of the kernel mode. **END** 

References

- *Understanding the LINUX KERNEL (third edition)* by Daniel P. Bovet and Marco Cesati
- *Glibc source v2.21*
- *Linux kernel source v5.0*

By: Shwetabh Srivastava

The author is a senior technical architect in the system software group of HCL Technologies Ltd. For the past few years he has been working on the design and development of Linux based operating systems.

support@efy.in

**Do you have a query,
suggestion or a complaint?**

**You can e-mail it to
support@efy.in
and we will take care
of the rest.**



electronics
FOR YOU
www.electronicsforu.com

OpenSource
THE COMPLETE MAGAZINE ON OPEN SOURCE FOR YOU
www.opensourceforu.com

EFYGROUP
YOURS SINCE 1969
www.efy.in