

If you want to pass specific flags to the invocation with Docker, you can pass the options to the Docker command as follows:

```
$ sudo docker run projectdiscovery/subfinder:latest -d google.com
```

Version

The '-version' option of subfinder prints the installed version of subfinder. As of writing this article, the latest version is v2.6.6.

```
$ subfinder -version
[INF] Current Version: v2.6.6
[INF] Subfinder Config Directory: /home/guest/.config/subfinder
```

Usage

The '-h' option of subfinder provides a quick summary and description of the various option flags supported by the tool.

```
$ subfinder -h
Subfinder is a subdomain discovery tool that discovers subdomains for websites by using passive online sources.

Usage:
  subfinder [flags]

Flags:
  -d, -domain string[]  domains to find subdomains for
  -dL, -list string      file containing list of domains for subdomain discovery

SOURCE:
  -s, -sources string[]  specific sources to use for discovery (-s crtsh,github). Use -ls to display all available sources.
  -recursive              use only sources that can handle subdomains recursively (e.g. subdomain.domain.tld vs domain.tld)
  -all                    use all sources for enumeration (slow)
  -es, -exclude-sources string[]  sources to exclude from enumeration (-es alienvault,zoomeyeapi)

FILTER:
  -m, -match string[]    subdomain or list of subdomain to match (file or comma separated)
  -f, -filter string[]    subdomain or list of subdomain to filter (file or comma separated)
  ...
```

Sources

The '-ls' or '-list-sources' option provides the list of all available sources as demonstrated below:

```
$ subfinder -ls
projectdiscovery.io

[INF] Current subfinder version v2.6.6 (latest)
[INF] Current list of available sources. [39]
[INF] Sources marked with an * need key(s) or token(s) to work.
[INF] You can modify /home/guest/.config/subfinder/provider-config.yaml to configure your keys/tokens.

alienvault
anubis
bevigil *
binaryedge *
bufferover *
c99 *
censys *
certspotter *
chaos *
...
waybackarchive
whoisxmlapi *
zoomeyeapi *
facebook *
builtwith *

Domain

You need to use the '-d' or '-domain string[]' option to specify the domain for which you want to find all the sub-domains. In the following example, we are searching for all the sub-domains for google.com.

$ subfinder -d google.com
...
googleproxy-66-249-80-193.google.com
googleproxy-64-233-172-24.google.com
www.google.com
firebase.rules.clients6.google.com
googleproxy-66-102-7-180.google.com
googleproxy-64-233-173-21.google.com
...
[INF] Enumerating subdomains for google.com
```