

```
[INF] Found 5875 subdomains for google.com in 2 seconds 434 milliseconds
```

Verbose

You can request for a more verbose output using the ‘-v’ option of subfinder as demonstrated below:

```
$ subfinder -d google.com -v
...
[alienvault] tuf-autopush.corp.google.com
[alienvault] staging-git.corp.google.com
[alienvault] docs-qa.corp.google.com
...
...
[crtsh] docs.google.com
[crtsh] mail.google.com
[crtsh] plus.google.com
...
[dnscumster] google-proxy-74-125-212-200.google.com
[dnscumster] google-proxy-64-233-172-200.google.com
[dnscumster] google-proxy-66-249-82-200.google.com
[INF] Found 5875 subdomains for google.com in 2 seconds 459 milliseconds
```

Match

The ‘-m’ or ‘-match’ option allows you to match only a specific string in the subdomain or list of subdomains. In the following example, we are searching for the subdomains that have ‘googleproxy’ in the name.

```
$ subfinder -m "googleproxy-*" -d google.com
...
googleproxy-66-249-82-201.google.com
googleproxy-64-233-172-33.google.com
googleproxy-66-102-7-221.google.com
googleproxy-66-249-84-51.google.com
...
googleproxy-66-249-84-91.google.com
googleproxy-66-249-88-34.google.com
googleproxy-64-233-172-180.google.com
[INF] Found 1761 subdomains for google.com in 4 seconds 692 milliseconds
```

Filter

You can omit certain patterns in the output using the ‘-f’ or ‘-filter string[]’ option to exclude a subdomain or list of subdomains. For example:

```
$ subfinder -f "googleproxy-*" -d google.com
...
maili0-f50.google.com
ratelimited-proxy-209-85-238-74.google.com
```

```
mailua0-f193.google.com
mailua0-f254.google.com
lens.google.com
ratelimited-proxy-203-208-38-180.google.com
mail-vs1-f10.google.com
[INF] Found 4114 subdomains for google.com in 4 seconds 700 milliseconds
```

Rate limit

The ‘-rl’ or ‘-rate-limit int’ option can restrict the number of HTTP requests sent per second to the website. It accepts an integer as an argument. For example:

```
$ subfinder -rl 2 -d google.com
...
rate-limited-proxy-74-125-150-100.google.com
rate-limited-proxy-108-177-69-120.google.com
r2.sn-npoene6.c.docs.google.com
mailio0-f171.google.com
...
[INF] Enumerating subdomains for google.com
[INF] Found 5875 subdomains for google.com in 10 seconds 343 millisecond
```

Concurrency

You can also specify the number of concurrent goroutines to be executed using the ‘-t int’ option. It accepts an integer argument, and the default value is 10.

```
$ subfinder -t 20 -d google.com
...
mailqt0-f203.google.com
mail-vs1-f110.google.com
cag.ext.google.com
ratelimited-proxy-66-249-91-10.google.com
...
[INF] Enumerating subdomains for google.com
[INF] Found 5875 subdomains for google.com in 11 seconds 616 milliseconds
```

Output

subfinder supports multiple output formats to show the results. The ‘-o’ or ‘-output string’ option writes the results to a file. For example:

```
$ subfinder -m "googleproxy-*" -d google.com -o /tmp/google.txt
```

The ‘-oJ’ or ‘-json’ flag converts each entry into a JSON structure that can be consumed by downstream applications.

```
$ subfinder -m "googleproxy-*" -d google.com -oJ
```