

```
...
{"host": "googleproxy-66-249-83-11.google.
com", "input": "google.com", "source": "anubis"}
{"host": "googleproxy-66-249-93-163.google.
com", "input": "google.com", "source": "anubis"}
{"host": "googleproxy-66-249-88-170.google.
com", "input": "google.com", "source": "anubis"}
{"host": "googleproxy-66-249-80-64.google.
com", "input": "google.com", "source": "anubis"}
[INF] Found 1761 subdomains for google.com in 3 seconds 562
milliseconds
```

You can also use the ‘-oD’ or ‘-output-dir string’ option to write the output to a directory. The ‘-cs’ or ‘-collect-sources’ option includes all the sources in the results when used only with the ‘-json’ flag. The ‘-oI’ or ‘-ip’ option includes the host IP address in the output.

Statistics

The information on source statistics can be obtained using the ‘-stats’ flag. A sample execution is given below:

```
$ subfinder -d google.com -stats
...
[INF] Found 5875 subdomains for google.com in 7 seconds 292
milliseconds
[INF] Printing source statistics for google.com
```

Source	Duration	Results	Errors
alienvault	7.291s	144	0
anubis	51ms	5197	0
builtwith	0s	0	0
crtsh	2.025s	105	0
digitorus	863ms	21	0
dnsdumpster	2.438s	1	0
hackertarget	1.31s	405	0
leakix	1.022s	2	0
virustotal	0s	0	0
...			

Configuration

The subfinder configuration is present in `~/.config/subfinder/config.yaml`. The first few lines of the file are given below:

```
# subfinder config file
# generated by https://github.com/projectdiscovery/goflags
# domains to find subdomains for
#domain: []
# file containing list of domains for subdomain discovery
#list:
# specific sources to use for discovery (-s crtsh,github).
use -ls to display all available sources.
#sources: []
```

```
# use only sources that can handle subdomains recursively
(e.g. subdomain.domain.tld vs domain.tld)
#recursive: false
# use all sources for enumeration (slow)
#all: false
# sources to exclude from enumeration (-es
alienvault,zoomeyeapi)
#exclude-sources: []
...
```

You can explicitly specify a configuration file using the ‘-config string’ option of subfinder. The provider configuration file is present in `~/.config/subfinder/provider-config.yaml`. For example:

```
bevigil: []
binaryedge: []
bufferover: []
builtwith: []
c99: []
censys: []
certspotter: []
chaos: []
chinaz: []
dnsdb: []
...
```

The ‘-pc’ or ‘-provider-config string’ option can be used to specify a different configuration file. The list of resolvers can be specified using the ‘-r string[]’ option. You can also include them in a file and pass it to the ‘-rL’ or ‘-rlist string’ option of subfinder.

Optimisation

The ‘-timeout int’ option makes the subfinder wait for the given number of seconds before timing out. The default value is 30 seconds. The ‘-max-time int’ option specifies the time in minutes to wait for the results. The default value is 10 minutes. If you do not want colour in the output, you can use the ‘-nc’ or ‘-no-color’ option. You can also use the tool as a library in your application code.

You are encouraged to read the subfinder documentation to learn more on its usage and flag options. 

References

- Subfinder Running, <https://docs.projectdiscovery.io/tools/subfinder/running>
- Subfinder GitHub, <https://github.com/projectdiscovery/subfinder>

 By: Shakthi Kannan

The author is a free software enthusiast.