

```
>>> lsc()
IPID_count      : Identify IP id values classes in a list
of packets
arpcachePoison  : Poison target's cache with (your
MAC,victim's IP) couple
arping          : Send ARP who-has requests to determine
which hosts are up
arpLeak         : Exploit ARP leak flaws, like NetBSD-
SA2017-002.
bind_layers     : Bind 2 layers on some specific fields'
values.
bridge_and_sniff : Forward traffic between interfaces if1
and if2, sniff and return
chexdump        : Build a per byte hexadecimal
representation
computeNIGroupAddr : Compute the NI group Address. Can take a
FQDN as input parameter
...
```

The default routes can be viewed using 'conf.route' as shown below:

```
>>> conf.route
Network      Netmask      Gateway      Iface
Output IP    Metric
0.0.0.0      0.0.0.0      192.168.111.1 wlp0s20f3
192.168.111.69 600
10.147.20.0  255.255.255.0 0.0.0.0      ztly546n2w
10.147.20.242 0
127.0.0.0    255.0.0.0    0.0.0.0      lo
127.0.0.1    1
169.254.0.0  255.255.0.0  0.0.0.0      virbr0
192.168.122.1 1000
172.17.0.0   255.255.0.0  0.0.0.0      docker0
172.17.0.1   0
192.168.111.0 255.255.255.0 0.0.0.0      wlp0s20f3
192.168.111.69 600
192.168.122.0 255.255.255.0 0.0.0.0      virbr0
192.168.122.1 0
```

The 'dir()' function is built-in and returns the names in the current scope as a list of strings:

```
>>> dir()
['In',
 'Out',
 '_',
 '_2',
 '_20',
 '_23',
 '_26',
 '_28',
```

```
'_32',
 '_35',
 ...
```

You can save the history of your commands in a session file using the 'save_session()' function as shown below:

```
>>> save_session("trace.scapy")
INFO: Use [trace.scapy] as session file
```

You can restore the session history from the file including the packets and data using the 'load_session()' function as follows:

```
>>> load_session("trace.scapy")
INFO: Loaded session [trace.scapy]
```

ICMP

Consider sending an Internet Control Message Protocol (ICMP) packet using the 'send()' function:

```
>>> send(IP(dst="www.google.com")/ICMP())
.
Sent 1 packets.
```

The 'sr()' function is used for sending and receiving packets. The 'sr1()' function in module scapy.sendrecv is used for receiving only one packet. We can rerun the ICMP request as shown below:

```
>>> p = sr1(IP(dst="www.google.com")/ICMP())
Begin emission:
Finished sending 1 packets.
*
Received 1 packets, got 1 answers, remaining 0 packets
```

The returned packet field values can be listed as follows:

```
>>> p
<IP version=4 ihl=5 tos=0x60 len=28 id=0 flags= frag=0
ttl=118 proto=icmp chksum=0x64e1 src=216.58.215.36
dst=192.168.111.152 |<ICMP type=echo-reply code=0
chksum=0xffff id=0x0 seq=0x0 |<Padding load='\x00\x00\x00\
x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00'
|>>>
```

A summary of the packet can be displayed using the 'summary()' function:

```
>>> p.summary()
'IP / ICMP 216.58.215.36 > 192.168.111.69 echo-reply 0 /
Padding'
```