

```

X-XSS-Protection: 0
X-Frame-Options: SAMEORIGIN
Set-Cookie: AEC=AQTF6HzW1KsaRuWA27yzb8WuUTE9eGyz1mSvPYE
LtTvc2yZWsfbX29nLg54; expires=Sat, 02-Nov-2024 17:14:24 GMT;
path=/; domain=.google.com; Secure; HttpOnly; SameSite=lax
Set-Cookie: NID=513=nz62fImI6wajdtIip_
abZGOKZ86o3mb2qHZS CeN2BivtYZelBDWsooM_JjAHgWzcE21fuNQyfppX_
KDu3IWC8WbZW1DXMEXKCjA9wbcmP8fbupmzD8p1t5P6guDdVuJbb8rf0hUozLt
4yrd9rIVTNEedx6ghqCQlqt7SZuvqtBA; expires=Tue, 05-Nov-2024
17:14:24 GMT; path=/; domain=.google.com; HttpOnly
Connection: close

```

URLs

You can provide a list of URLs to be scanned from a file using the `--input-file` option as shown below:

```
$ whatweb --input-file urls.txt
```

Logging

You can also log the output to a file and other external entities rather than the console. The supported logging outputs are given below:

Option	Entity
<code>--log-json</code>	JSON
<code>--log-sql</code>	SQL INSERT commands
<code>--log-sql-create</code>	Create SQL database tables
<code>--log-xml</code>	XML
<code>--log-magictree</code>	MagicTree XML
<code>--log-object</code>	Ruby object inspection format
<code>--log-mongo-database</code>	MongoDB database
<code>--log-mongo-collection</code>	MongoDB collection
<code>--log-elastic-index</code>	Elasticsearch index

Embedded devices

The WhatWeb command can also be run on embedded devices. The following is an example from scanning a TP-Link router device:

```

$ whatweb -v 10.0.0.5
WhatWeb report for http://10.0.0.5
Status    : 200 OK
Title     : <None>
IP        : 10.0.0.5
Country   : RESERVED, ZZ

Summary   : Cookies[JSESSIONID], Email[zhujunjie@tp-link.net], Frame, HttpOnly[JSESSIONID], JQuery[1.8.3], PasswordField, Script[text/javascript]

```

Detected Plugins:

[Cookies]

Display the names of cookies in the HTTP headers. The values are not returned to save on space.

```
String      : JSESSIONID
```

The router has an email contact for reference, and hence the same is provided in the output:

[Email]

Extract email addresses. Find valid email address and syntactically invalid email addresses from mailto: link tags. We match syntactically invalid links containing mailto: to catch anti-spam email addresses, eg. bob at gmail.com. This uses the simplified email regular expression from <http://www.regular-expressions.info/email.html> for valid email address matching.

```
String      : zhujunjie@tp-link.net
```

iframes, JavaScript libraries, and HTTP headers are also detected as illustrated below:

[Frame]

This plugin detects instances of frame and iframe HTML elements.

[HttpOnly]

If the HttpOnly flag is included in the HTTP set-cookie response header and the browser supports it then the cookie

cannot be accessed through client side script - More Info:

http://en.wikipedia.org/wiki/HTTP_cookie

```
String      : JSESSIONID
```

[JQuery]

A fast, concise, JavaScript that simplifies how to traverse

HTML documents, handle events, perform animations, and add

```
AJAX.
```

```
Version     : 1.8.3
```

```
Website     : http://jquery.com/
```

[PasswordField]

find password fields