

```
[ Script ]
    This plugin detects instances of script HTML elements
    and
    returns the script language/type.

    String      : text/javascript

HTTP Headers:
    HTTP/1.1 200 OK
    Content-Type: text/html; charset=utf-8
    Content-Length: 62924
    Set-Cookie: JSESSIONID=deleted; Expires=Thu, 01 Jan 1970
00:00:01 GMT; Path=/; HttpOnly
    Connection: close
```

Scan modes

The different scan levels are given below:

Level	Aggression
1	Passive
2	Polite (not implemented)
3	Impolite
4	Aggressive

The aggressive mode level can be set to the highest value of 3, and along with the increased verbosity level you can get a more detailed scan output. For example:

```
$ whatweb -vv -a 3 google.com
http://google.com/ [301]
redirect 1 from http://google.com to http://www.google.com/
Identifying: http://google.com
HTTP-Status: 301
[["Country", [{"string"=>"UNITED STATES", :module=>"US",
:certainty=>100}]],
["HTTPServer", [{"name=>"server string", :string=>"gws",
:certainty=>100}]],
["IP", [{"string"=>"142.250.196.46", :certainty=>100}]],
["RedirectLocation",
[{"name=>"location", :string=>"http://www.google.com/",
:certainty=>100}]],
["Title", [{"name=>"page title", :string=>"301 Moved",
:certainty=>100}]],
["UncommonHeaders",
[{"name=>"headers",
:string=>"content-security-policy-report-only",
:certainty=>100}]],
["X-Frame-Options", [{"string=>"SAMEORIGIN",
:certainty=>100}]],
["X-XSS-Protection", [{"string=>"0", :certainty=>100}]]]
```

WhatWeb report for <http://google.com>

```
Status   : 301 Moved Permanently
Title    : 301 Moved
IP       : 142.250.196.46
Country  : UNITED STATES, US
```

```
Summary  : HTTPServer[gws], RedirectLocation[http://www.
google.com/], UncommonHeaders[content-security-policy-report-
only], X-Frame-Options[SAMEORIGIN], X-XSS-Protection[0]
...
```

Detected Plugins:

[Cookies]

Display the names of cookies in the HTTP headers. The values are not returned to save on space.

```
String    : 1P_JAR
{:certainty=>100, :string=>"1P_JAR"}
String    : AEC
{:certainty=>100, :string=>"AEC"}
String    : NID
{:certainty=>100, :string=>"NID"}
...
```

Performance

WhatWeb also comes with several options to increase the performance of the scan:

Option	Description
<code>--max-threads</code>	Number of simultaneous reads
<code>--read-timeout</code>	Time in seconds (Default: 30s)
<code>--open-timout</code>	Time in seconds (Default: 15s)
<code>--wait</code>	Seconds to wait between connections

You are encouraged to read the manual page of WhatWeb to learn more on its usage, plugins, and command arguments. 

References

- WhatWeb Wiki, <https://github.com/urbanadventurer/whatweb/wiki>
- WhatWeb GitHub repository, <https://github.com/urbanadventurer/WhatWeb>
- Home page, <https://www.whatweb.net/>
- Features, <https://github.com/urbanadventurer/WhatWeb/wiki/Features>

 By: Shakthi Kannan

The author is a free software enthusiast.