

ngrok by @inconsreveable

```

Session Status      online
Account             Prarthana (Plan: Free)
Update              update available (version 2.3.41, Ctrl-U to update)
Version             2.3.40
Region              United States (us)
Web Interface       http://127.0.0.1:4040
Forwarding           http://9688-103-156-19-229.ngrok-free.app -> http://localhost:8080
Forwarding           https://9688-103-156-19-229.ngrok-free.app -> http://localhost:8080

Connections
  ttl    opn    rt1    rt5    p50    p90
    0     0     0.00   0.00   0.00   0.00

```

Figure 2: ngrok setup

of commands to install Jenkins X on your Kubernetes cluster. This can vary based on the installation method you choose—whether it's using the jx CLI directly or Helm charts provided by Jenkins X.

▪ Helm

Step 1: Use this command to download the most recent version:

```
curl -fsSL -o get_helm.sh https://raw.githubusercontent.com/helm/helm/main/scripts/get-helm-3
```

Step 2: Change the permission:

```
chmod 700 get_helm.sh
```

Step 3: Execute the script:

```
./get_helm.sh
```

Step 4: Check for version:

```
helm version
```

▪ Minikube

Step 1: Install kubectl.

Step 1.1. Use this command to download the most recent version:

```
curl -LO "https://dl.k8s.io/release/${curl -L -s https://dl.k8s.io/release/stable.txt}/bin/linux/amd64/kubectl"
```

Step 1.2. Install kubectl:

```
sudo install -o root -g root -m 0755 kubectl /usr/local/bin/kubectl
```

Step 1.3. Verify that the version you installed is current by running a test:

```
kubectl version --client
```

Step 2: Install minikube. Using a binary download, install the most recent minikube stable release on x86-64 Linux.

```
curl -LO https://storage.googleapis.com/minikube/releases/latest/minikube-
```

```
linux-amd64
```

```
sudo install minikube-linux-amd64 /usr/local/bin/minikube
```

Step 3: Start minikube:

```
minikube start --cpus 4 --memory 6048 --disk-size=100g --addons=ingress
```

▪ GitOps

For the purpose of installing and upgrading Jenkins X and any other components in any environment, Jenkins X 3.x makes use of a Git

```

1 ingress:
2   # allows you to specify custom hosts
3   customHosts:
4     # specify your ngrok custom domain here
5     # such as
6     # hook: "myuniqueid.ngrok.io"
7     # so that webhooks from, say, github.com, will work to your local laptop
8     hook: "9688-103-156-19-229.ngrok.io"
9
10 kaniko:
11   # lets support insecure docker registries so that we
12   # can use the local docker-registry chart
13   flags: "--insecure"

```

Figure 3: Addition of hook in values.yml

```

prarthana@prarthana-Inspiron-3501:~/gitops/gitops$ git add .
prarthana@prarthana-Inspiron-3501:~/gitops/gitops$ git commit -m ngrok
[main d8c98dd] ngrok
4 files changed, 6 insertions(+), 2 deletions(-)
create mode 160000 https://github.com/prarthanaus0597/scientific_calculator.git
create mode 160000 php-helloworld
prarthana@prarthana-Inspiron-3501:~/gitops/gitops$ git push
Username for 'https://github.com': prarthanaus0597
Password for 'https://prarthanaus0597@github.com':
Enumerating objects: 24, done.
Counting objects: 100% (24/24), done.
Delta compression using up to 8 threads
Compressing objects: 100% (10/10), done.
Writing objects: 100% (14/14), 1014 bytes | 507.00 KiB/s, done.
Total 14 (delta 7), reused 0 (delta 0), pack-reused 0
remote: Resolving deltas: 100% (7/7), completed with 7 local objects.
To https://github.com/prarthanaus0597/gitops.git
   e51c26b..d8c98dd  main -> main
prarthana@prarthana-Inspiron-3501:~/gitops/gitops$

```

Figure 4: Git commit