

Name	Labels	Type	Cluster IP	External IP	Ports	Age	Selector
bucketrepo	chart.bucketrepo, gitops.jenkins-x.io	ClusterIP	10.111.208.31	<none>	80/TCP	17d	app.bucketrepo-bucketrepo
docker-registry	app.docker-registry, chart.docker-registry-2.2.2	ClusterIP	10.106.113.57	<none>	80/TCP	17d	app.docker-registry, release.docker-registry
hook	chart.lighthouse, gitops.jenkins-x.io	ClusterIP	10.106.232.185	<none>	80/TCP	17d	app.lighthouse-webhooks
jx-pipelines-visualizer	app.kubernetes.io/name=jx-pipelines-visualizer, app.kubernetes.io/instance=jx-pipelines-visualizer	ClusterIP	10.101.91.177	<none>	80/TCP	17d	app.kubernetes.io/name=jx-pipelines-visualizer, app.kubernetes.io/instance=jx-pipelines-visualizer
lighthouse-keeper	gitops.jenkins-x.io/pipeline.namespaces	ClusterIP	10.105.206.12	<none>	80/TCP	17d	app.lighthouse-keeper
lighthouse-tekton-controller	chart.lighthouse, gitops.jenkins-x.io	ClusterIP	10.111.43.213	<none>	8080/TCP	17d	app.lighthouse-tekton-controller

Figure 9: Services information in JX

and administration is slated for future integration.

If you have a recent run of the jx binaries, you can use the Jenkins X plugins to run Octant:

```
$ jx ui
```

This will start Octant for you after downloading the Octant binaries and octant-jx plugin.

Running Jenkins X

1. Configure the ngrok URL and ensure ngrok stays operational.

```
$ ngrok 8080
```

You can see the output in Figure 2.

2. Paste a unique ID before `.ngrok-free.app` to `values.yml` file for hook key and push it to GitHub. The `values.yml` file is present in the path `/home/prarthana/gitops/charts/jenkins-x/jxboot-helmfile-resources/values.yml`. `gitops` is the directory where the repository is cloned during the installation of GitOps.

3. Start the minikube:

```
minikube start --cpus 4 --memory 6048 --disk-size=100g --addons=ingress
```

4. Start GitOps. In order to enable insecure Git repositories, you might need

to use the `git config` command in the Git operator and boot job if you are utilising an on-premises Git repository. You may use the `--setup` parameter to pass along any Git configuration instructions when installing the Git operator.

Note: Set up the token for the GitHub access from GitHub developer settings.

```
export GIT_USERNAME=prarthanaus0597
export GIT_TOKEN=ghp_uy9uRM5gmQGoBbuH58D2mpWYU1Yr5M22HTWv
jx admin operator --setup "git config --global http.sslVerify false"
(can also be done by jx admin operator --username mygituser --token mygittoken)
```

Once completed you get the success message on the terminal as shown in Figure 5.

5. Once Jenkins X is installed, run the following command to enable webhooks via ngrok:

```
prarthana@prarthana-Inspiron-3501:~/gitops/gitops$ kubectl port-forward svc/hook 4040:80
Forwarding from [::1]:4040 -> 8080
```

6. You can use the following command to view the boot job logs at any time:

```
$ jx admin log
```

Name	Labels	Data	Age
config	gitops.jenkins-x.io/pipeline.namespaces	1	17d
docker-registry-config	app.docker-registry, chart.docker-registry-2.2.2	1	17d
ingress-config	gitops.jenkins-x.io/pipeline.namespaces	5	17d
jenkins-x-docker-registry	gitops.jenkins-x.io/pipeline.namespaces	2	17d
jenkins-x-extensions	gitops.jenkins-x.io/pipeline.namespaces	2	17d
jx-install-config	gitops.jenkins-x.io/pipeline.namespaces	1	17d

Figure 10: ConfigMaps information in JX