

diff config.json

```
3c3
<   "columns": 2,
---
>   "columns": 3,
5,7d4
<   { "type": "PING", "params": {"hostname": "127.0.0.1"}},
<   { "type": "PORT", "params": {"hostname": "127.0.0.1",
"port": 8080}},
<   { "type": "HTTP-STATUS", "params": {"url": "https://
google.com"}},
10c7
<     "label": "localhost PING/PORT/HTTP Tests",
---
>     "label": "opensearch PING/PORT/HTTP Tests",
12,30c9,28
<     {
<       "type": "PING",
<       "params": {
<         "hostname": "129.0.0.1"
<     }
<   },
<   {
<     "type": "PORT",
<     "params": {
<       "hostname": "127.0.0.1",
<       "port": 8080
<     }
<   },
<   {
<     "type": "HTTP-STATUS",
<     "params": {
<       "url": "http://localhost:8080"
<     }
<   }
---
>   {"type": "PING", "params": {"hostname": "opensearch"}},
```

```
>      {"type": "PORT", "params": {"hostname": "opensearch",
"port": 9200}},
>      {"type": "PORT", "params": {"hostname": "opensearch",
"port": 9600}},
>      {"type": "HTTP-STATUS", "params": {"url": "https://
admin:admin@opensearch:9200"}}
>  ]
> },
> {
>   "type": "GROUP",
>   "label": "kafka PING/PORT Tests",
>   "tiles": [
>     {"type": "PING", "params": {"hostname": "kafka"}},
>     {"type": "PORT", "params": {"hostname": "kafka",
"port": 9092}}
>   ]
> },
> {
>   "type": "GROUP",
>   "label": "redis PING/PORT Tests",
>   "tiles": [
>     {"type": "PING", "params": {"hostname": "redis"}},
>     {"type": "PORT", "params": {"hostname": "redis",
"port": 6379}}
```

Use the commands we used earlier for launching the previous demo and copying the Monitoror config respectively. You should see the Monitoror wallboard with the new server tiles as shown in Figure 4.

By now you should be feeling at home with Monitoror and its elegant capabilities to quickly up and run a monitoring wallboard. The following command cleans up the whole running stack once you're done playing with Monitoror:

```
docker run -it --rm -v /var/run/docker.sock:/var/run/docker.
sock:ro -v ./monitoror_stack.yml:/etc/compose/monitoror_
stack.yml:ro docker docker compose -f /etc/compose/monitoror_
stack.yml down
```



Figure 4: Monitoror wallboard for multiple service checks