

diff vigil_stack.yml

```

8a9,33
> opensearch:
>   image: opensearchproject/opensearch:${OSRHTAG:-latest}
>   environment:
>     - "discovery.type=single-node"
>   restart: unless-stopped
>
> kafka:
>   image: apache/kafka-native
>   environment:
>     KAFKA_LISTENERS: CONTROLLER://localhost:9091,HOST://0
.0.0.0:9092,DOCKER://0.0.0.0:9093
>     KAFKA_ADVERTISED_LISTENERS: HOST://
localhost:9092,DOCKER://kafka:9093
>     KAFKA_LISTENER_SECURITY_PROTOCOL_MAP: CONTROLLER:PLAI
NTEXT,DOCKER:PLAINTEXT,HOST:PLAINTEXT
>     KAFKA_NODE_ID: 1
>     KAFKA_PROCESS_ROLES: broker,controller
>     KAFKA_CONTROLLER_LISTENER_NAMES: CONTROLLER
>     KAFKA_CONTROLLER_QUORUM_VOTERS: 1@localhost:9091
>     KAFKA_INTER_BROKER_LISTENER_NAME: DOCKER
>     KAFKA_OFFSETS_TOPIC_REPLICATION_FACTOR: 1
>   restart: unless-stopped
>
> redis:
>   image: redis:${RDSSTAG:-latest}
>   command: "redis-server --save 60 1 --loglevel warning"
>   restart: unless-stopped
>

```

Now change the previous configuration file as shown in the diff below including probes covering the Kafka, OpenSearch and Redis containers:

diff config.cfg

```

30,34d29
< push_delay_dead = 20
< push_system_cpu_sick_above = 0.90
< push_system_ram_sick_above = 0.90
< script_interval = 300
< local_delay_dead = 40
45,46c40,41
< id = "ping"
< label = "PING"
---
> id = "kafka"
> label = "KAFKA"
48,49c43,44
< id = "invalidiping"

```

```

< label = "Invalid IP Ping"
---
> id = "kafkaping"
> label = "Kafka Ping"
51c46,53
< replicas = ["icmp://129.0.0.1"]
---
> replicas = ["icmp://kafka"]
> reveal_replica_name = true
> [[probe.service.node]]
> id = "kafkaport9092"
> label = "Kafka Port 9092"
> mode = "poll"
> reveal_replica_name = true
> replicas = ["tcp://kafka:9092"]
54,55c56,57
< id = "port"
< label = "PORT"
---
> id = "opensearch"
> label = "OPENSEARCH"
57,58c59,60
< id = "localhostport"
< label = "Localhost Port 8080 Probe"
---
> id = "opensearchping"
> label = "Opensearch Ping"
60c62,86
< replicas = ["tcp://localhost:8080"]
---
> reveal_replica_name = true
> replicas = ["icmp://opensearch"]
> [[probe.service.node]]
> id = "opensearchport9200"
> label = "Opensearch Port 9200"
> mode = "poll"
> reveal_replica_name = true
> replicas = ["tcp://opensearch:9200"]
> [[probe.service.node]]
> id = "opensearchhttp9200"
> label = "Opensearch Http 9200"
> mode = "script"
> reveal_replica_name = true
> scripts = [
> '''
> /usr/bin/curl -k https://admin:admin@opensearch:9200

```