

```
(arp or (ether[14:4]=0xaaaa0300 and ether[20:2]=0x0806)
or (ether[12:2]=0x8100 and ether[16:2]=0x0806) or
(ether[12:2]=0x8100 and ether[18:4]=0xaaaa0300 and
ether[24:2]=0x0806))"
DEBUG: Loaded 30082 IEEE OUI/Vendor entries from ieee-oui.
txt.
DEBUG: Loaded 4575 IEEE IAB/Vendor entries from /usr/share/
arp-scan/ieee-iab.txt.
DEBUG: Loaded 6 MAC/Vendor entries from /usr/share/arp-scan/
mac-vendor.txt.
DEBUG: pkt len=64 bytes, bandwidth=256000 bps, interval=2000
us
Starting arp-scan 1.9.7 with 1 hosts (https://github.com/
royhills/arp-scan)
--- Sending packet #1 to host 10.0.0.100 tmo 500000
--- Pass 1 complete
--- Sending packet #2 to host 10.0.0.100 tmo 750000
--- Received packet #1 from 10.0.0.100
10.0.0.100 00:0a:95:9d:68:16 (Unknown: locally administered)
--- Removing host 10.0.0.100 - Received 60 bytes
```

1 packets received by filter, 0 packets dropped by kernel
Ending arp-scan 1.9.7: 1 hosts scanned in 0.717 seconds (1.39 hosts/sec). 1 responded

```
$ sudo arp-scan -vvv 10.0.0.100
Interface: eth0, type: EN10MB, MAC: d4:ba:ba:af:ff:f1, IPv4:
10.0.0.103
DEBUG: pcap filter string: "ether dst d4:ba:ba:af:ff:f1 and
(arp or (ether[14:4]=0xaaaa0300 and ether[20:2]=0x0806)
or (ether[12:2]=0x8100 and ether[16:2]=0x0806) or
(ether[12:2]=0x8100 and ether[18:4]=0xaaaa0300 and
ether[24:2]=0x0806))"
DEBUG: Loaded 30082 IEEE OUI/Vendor entries from ieee-oui.
txt.
DEBUG: Loaded 4575 IEEE IAB/Vendor entries from /usr/share/
arp-scan/ieee-iab.txt.
DEBUG: Loaded 6 MAC/Vendor entries from /usr/share/arp-scan/
mac-vendor.txt.
DEBUG: pkt len=64 bytes, bandwidth=256000 bps, interval=2000
us
Starting arp-scan 1.9.7 with 1 hosts (https://github.com/
royhills/arp-scan)
Host List:
```

```
Entry IP Address
1 10.0.0.100
```

Total of 1 host entries.

```
--- Sending packet #1 to host 10.0.0.100 tmo 500000
--- Received packet #1 from 10.0.0.100
```

```
10.0.0.100 00:0a:95:9d:68:16 (Unknown: locally administered)
--- Removing host 10.0.0.100 - Received 60 bytes
```

1 packets received by filter, 0 packets dropped by kernel
Ending arp-scan 1.9.7: 1 hosts scanned in 0.320 seconds (3.12 hosts/sec). 1 responded

The maximum number of v's allowed are three.

Interface

You can explicitly specify the network interface to scan using the *-I* option. For example:

```
$ sudo arp-scan --localnet -I wlan0
Interface: wlan0, type: EN10MB, MAC: 58:6c:25:ed:5d:d7, IPv4:
10.0.0.105
Starting arp-scan 1.9.7 with 256 hosts (https://github.com/
royhills/arp-scan)
10.0.0.1 2c:54:91:88:c9:e3 (Unknown)
10.0.0.100 8c:1f:64:a2:d0:01 IEEE Registration Authority
```

2 packets received by filter, 0 packets dropped by kernel
Ending arp-scan 1.9.7: 256 hosts scanned in 1.959 seconds (130.68 hosts/sec). 2 responded

Netmask

arp-scan scans all the possible hosts available in the network. In the above example, it searched for 256 hosts. You can explicitly specify a netmask to limit the range as indicated below:

```
$ sudo arp-scan 10.0.0.103/28
Interface: eth0, type: EN10MB, MAC: d4:ba:ba:af:ff:f1, IPv4:
10.0.0.104
WARNING: host part of 10.0.0.103/28 is non-zero
Starting arp-scan 1.9.7 with 16 hosts (https://github.com/
royhills/arp-scan)
10.0.0.100 8c:1f:64:a2:d0:01 IEEE Registration Authority
```

3 packets received by filter, 0 packets dropped by kernel
Ending arp-scan 1.9.7: 16 hosts scanned in 1.466 seconds (10.91 hosts/sec). 1 responded

Hosts

You can also explicitly list the hosts that you want to scan with the *arp-scan* command. For example:

```
$ sudo arp-scan --interface=eth0 10.0.0.1 10.0.0.100
10.0.0.103
Interface: eth0, type: EN10MB, MAC: d4:ba:ba:af:ff:f1, IPv4:
10.0.0.104
Starting arp-scan 1.9.7 with 3 hosts (https://github.com/
```