

```
try.all.packages = getOption("help.try.all.packages"),
  help_type = getOption("help_type"))
```

Arguments:

`topic`: usually, a name or character string specifying the topic for which help is sought. A character string (enclosed in explicit single or double quotes) is always taken as naming a topic.

If the value of `'topic'` is a length-one character vector the topic is taken to be the value of the only element. Otherwise `'topic'` must be a name or a reserved word (if syntactically valid) or character string.

See `'Details'` for what happens if this is omitted.

...

You can search for specific help using the `help.search` function, as shown below:

```
> help.search("histogram")
```

Help files with alias or concept or title matching `'histogram'` using fuzzy matching:

```
graphics::hist          Histograms
graphics::hist.POSIXt   Histogram of a Date or Date-Time
Object
graphics::plot.histogram
                        Plot Histograms
  Aliases: plot.histogram, lines.histogram
grDevices::nclass.Sturges
                        Compute the Number of Classes for a
Histogram
KernSmooth::dpih        Select a Histogram Bin Width
lattice::histogram       Histograms and Kernel Density Plots
  Aliases: histogram, histogram.factor, histogram.numeric,
            histogram.formula
lattice::panel.histogram
                        Default Panel Function for histogram
  Aliases: panel.histogram
lattice::prepanel.default.bwplot
                        Default Prepanel Functions
  Aliases: prepanel.default.histogram
MASS::hist.scott         Plot a Histogram with Automatic Bin
Width
                        Selection
MASS::ldahist            Histograms or Density Plots of
Multiple Groups
```

```
MASS::truehist          Plot a Histogram
```

Type `'?PKG::FOO'` to inspect entries `'PKG::FOO'`, or `'TYPE?PKG::FOO'` for entries like `'PKG::FOO-TYPE'`.

The information on operators (arithmetic, for example) can be obtained with the question mark symbol followed by the operator, enclosed within back quotes as illustrated below:

```
> ?`%`
```

```
Arithmetic              package:base          R
Documentation
```

Arithmetic Operators

Description:

These unary and binary operators perform arithmetic on numeric or complex vectors (or objects which can be coerced to them).

Usage:

```
+ x
- x
x + y
x - y
x * y
x / y
x ^ y
x %% y
x %/% y
```

Arguments:

`x`, `y`: numeric or complex vectors or objects which can be coerced to such, or other objects for which methods have been written.

The `'base'` package in R comes with a lot of demos that you can try out from the R console. You can list them using the `demo` function:

```
> demo()
Demos in package 'base':
```

```
error.catching          More examples on catching and handling
```